

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Commissioner
 US Department of Commerce
 United States Patent and Trademark
 Office, PCT
 2011 South Clark Place Room
 CP2/5C24
 Arlington, VA 22202
 ETATS-UNIS D'AMERIQUE
 in its capacity as elected Office

Date of mailing (day/month/year) 15 November 2000 (15.11.00)	Applicant's or agent's file reference PAT 99409aPC
International application No. PCT/IB00/00229	Priority date (day/month/year) 24 February 1999 (24.02.99)
International filing date (day/month/year) 24 February 2000 (24.02.00)	
Applicant HONKO, Harri et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:
 21 September 2000 (21.09.00)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer Zakaria EL KHODARY Telephone No.: (41-22) 338.83.38
---	--

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference PAT 99409aPC	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/IB 00/ 00229	International filing date (day/month/year) 24/02/2000	(Earliest) Priority Date (day/month/year) 24/02/1999
Applicant NOKIA MOBILE PHONES LIMITED		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer-readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☐ the text is approved as submitted by the applicant.

☒ the text has been established by this Authority to read as follows:

TELECOMMUNICATION SERVICES IDENTIFICATION IN A GATEWAY

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

3

☐ None of the figures.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/38 H04Q11/04 H04Q3/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 34437 A (TELEFONAKTIEBOLAGET L M ERICSSON) 18 September 1997 (1997-09-18)	1,6-10, 12-21, 26-30, 32-42
Y	abstract	
A	page 7, line 4 -page 8, line 11 claim 1; figure 1	2-4, 22-24 5,11,25, 31

	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 July 2000

Date of mailing of the international search report

25/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gijssels, W

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 843 454 A (LUCENT TECHNOLOGIES INC) 20 May 1998 (1998-05-20) abstract column 4, line 39 -column 5, line 14 claims 1,2; figure 1 ----	1,6,9, 16-21, 26,29, 33-42
Y	WO 98 58475 A (TOSHIBA K K) 23 December 1998 (1998-12-23) abstract & EP 0 921 659 A (TOSHIBA K K) 9 June 1999 (1999-06-09) column 12, line 8 -column 13, line 10 claims 28,31,34; figures 1-7 ----	2-4, 22-24
A	EP 0 771 095 A (AT & T CORP) 2 May 1997 (1997-05-02) abstract claims 1-3; figures 1,2 ----	1-42
A	LINDBERGH D: "THE H.324 MULTIMEDIA COMMUNICATION STANDARD" IEEE COMMUNICATIONS MAGAZINE, vol. 34, no. 12, 1 December 1996 (1996-12-01), pages 46-51, XP000636453 PISCATAWAY, NJ, US ISSN: 0163-6804 ----	
P,X	DE 198 15 430 A (DEUTSCHE TELEKOM MOBILNET GMBH) 14 October 1999 (1999-10-14) abstract column 3, line 16-41 claim 1; figures 1A,1B ----	1,6-10, 12-21, 26-30, 32-42
E	US 6 073 018 A (SALLBERG K) 6 June 2000 (2000-06-06) abstract column 7, line 8 -column 8, line 38 tables 2,3A,3B claims 1,6,9; figure 1 -----	1-4, 6-10, 12-24, 26-30, 32-42

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 00/00229

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9734437	A	18-09-1997	US 5890064 A	30-03-1999
			AU 711632 B	21-10-1999
			AU 2049097 A	01-10-1997
			CA 2247979 A	18-09-1997
			CN 1217861 A	26-05-1999
			EP 0886984 A	30-12-1998
EP 0843454	A	20-05-1998	JP 10190743 A	21-07-1998
WO 9858475	A	23-12-1998	CN 1234933 T	10-11-1999
			EP 0921659 A	09-06-1999
EP 0771095	A	02-05-1997	US 5724355 A	03-03-1998
			CA 2184209 A	25-04-1997
			JP 9214564 A	15-08-1997
DE 19815430	A	14-10-1999	AU 4132499 A	25-10-1999
			WO 9952255 A	14-10-1999
US 6073018	A	06-06-2000	AU 1722199 A	28-06-1999
			WO 9930518 A	17-06-1999

PATENT COOPERATION TREATY

From the INTERNATIONAL SEARCHING AUTHORITY

Administrative Record

PCT

To:
NOKIA IPR DEPARTMENT
Nokia House
Attn. JEFFERY, K.
Summit Avenue, Southwood
Farnborough
Hamps. GU14 0NG
UNITED KINGDOM

☒ File Record
☒ ☐ ☐
27 JUL 2000
☐ Renewal
☒ Citations
☐ Inv Award

NOTIFICATION OF TRANSMITTAL OF
THE INTERNATIONAL SEARCH REPORT
OR THE DECLARATION

(PCT Rule 44.1)

☐ Letters
☐ CC

Date of mailing
(day/month/year) 25/07/2000

Applicant's or agent's file reference
PAT 99409aPC

FOR FURTHER ACTION See paragraphs 1 and 4 below

International application No.
PCT/IB 00/00229

International filing date
(day/month/year) 24/02/2000

Applicant
NOKIA MOBILE PHONES LIMITED

1. ☒ The applicant is hereby notified that the International Search Report has been established and is transmitted herewith.

Filing of amendments and statement under Article 19:

The applicant is entitled, if he so wishes, to amend the claims of the International Application (see Rule 46):

When? The time limit for filing such amendments is normally 2 months from the date of transmittal of the International Search Report; however, for more details, see the notes on the accompanying sheet.

Where? Directly to the International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland
Facsimile No.: (41-22) 740.14.35

For more detailed instructions, see the notes on the accompanying sheet.

2. ☐ The applicant is hereby notified that no International Search Report will be established and that the declaration under Article 17(2)(a) to that effect is transmitted herewith.

3. ☐ **With regard to the protest** against payment of (an) additional fee(s) under Rule 40.2, the applicant is notified that:

☐ the protest together with the decision thereon has been transmitted to the International Bureau together with the applicant's request to forward the texts of both the protest and the decision thereon to the designated Offices.

☐ no decision has been made yet on the protest; the applicant will be notified as soon as a decision is made.

4. **Further action(s):** The applicant is reminded of the following:

Shortly after **18 months** from the priority date, the international application will be published by the International Bureau. If the applicant wishes to avoid or postpone publication, a notice of withdrawal of the international application, or of the priority claim, must reach the International Bureau as provided in Rules 90bis.1 and 90bis.3, respectively, before the completion of the technical preparations for international publication.

Within **19 months** from the priority date, a demand for international preliminary examination must be filed if the applicant wishes to postpone the entry into the national phase until 30 months from the priority date (in some Offices even later).

Within **20 months** from the priority date, the applicant must perform the prescribed acts for entry into the national phase before all designated Offices which have not been elected in the demand or in a later election within 19 months from the priority date or could not be elected because they are not bound by Chapter II.

Name and mailing address of the International Searching Authority



European Patent Office, P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Theresia Van Deursen

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference PAT 99409aPC	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/IB 00/ 00229	International filing date (day/month/year) 24/02/2000	(Earliest) Priority Date (day/month/year) 24/02/1999
Applicant NOKIA MOBILE PHONES LIMITED		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☐ the text is approved as submitted by the applicant.

☒ the text has been established by this Authority to read as follows:

TELECOMMUNICATION SERVICES IDENTIFICATION IN A GATEWAY

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

3

☐ None of the figures.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/38 H04Q11/04 H04Q3/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 34437 A (TELEFONAKTIEBOLAGET L M ERICSSON) 18 September 1997 (1997-09-18)	1,6-10, 12-21, 26-30, 32-42
	abstract	
	page 7, line 4 -page 8, line 11	
	claim 1; figure 1	
Y		2-4, 22-24
A		5,11,25, 31
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 July 2000

Date of mailing of the international search report

25/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gijssels, W

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>EP 0 843 454 A (LUCENT TECHNOLOGIES INC) 20 May 1998 (1998-05-20)</p> <p>abstract column 4, line 39 -column 5, line 14 claims 1,2; figure 1</p> <p style="text-align: center;">---</p>	<p>1,6,9, 16-21, 26,29, 33-42</p>
Y	<p>WO 98 58475 A (TOSHIBA K K) 23 December 1998 (1998-12-23)</p> <p>abstract & EP 0 921 659 A (TOSHIBA K K) 9 June 1999 (1999-06-09) column 12, line 8 -column 13, line 10 claims 28,31,34; figures 1-7</p> <p style="text-align: center;">---</p>	<p>2-4, 22-24</p>
A	<p>EP 0 771 095 A (AT & T CORP) 2 May 1997 (1997-05-02)</p> <p>abstract claims 1-3; figures 1,2</p> <p style="text-align: center;">---</p>	<p>1-42</p>
A	<p>LINDBERGH D: "THE H.324 MULTIMEDIA COMMUNICATION STANDARD" IEEE COMMUNICATIONS MAGAZINE, vol. 34, no. 12, 1 December 1996 (1996-12-01), pages 46-51, XP000636453 PISCATAWAY, NJ, US ISSN: 0163-6804</p> <p style="text-align: center;">---</p>	
P,X	<p>DE 198 15 430 A (DEUTSCHE TELEKOM MOBILNET GMBH) 14 October 1999 (1999-10-14)</p> <p>abstract column 3, line 16-41 claim 1; figures 1A,1B</p> <p style="text-align: center;">---</p>	<p>1,6-10, 12-21, 26-30, 32-42</p>
E	<p>US 6 073 018 A (SALLBERG K) 6 June 2000 (2000-06-06)</p> <p>abstract column 7, line 8 -column 8, line 38 tables 2,3A,3B claims 1,6,9; figure 1</p> <p style="text-align: center;">-----</p>	<p>1-4, 6-10, 12-24, 26-30, 32-42</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 00/00229

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9734437 A	18-09-1997	US 5890064 A AU 711632 B AU 2049097 A CA 2247979 A CN 1217861 A EP 0886984 A	30-03-1999 21-10-1999 01-10-1997 18-09-1997 26-05-1999 30-12-1998
EP 0843454 A	20-05-1998	JP 10190743 A	21-07-1998
WO 9858475 A	23-12-1998	CN 1234933 T EP 0921659 A	10-11-1999 09-06-1999
EP 0771095 A	02-05-1997	US 5724355 A CA 2184209 A JP 9214564 A	03-03-1998 25-04-1997 15-08-1997
DE 19815430 A	14-10-1999	AU 4132499 A WO 9952255 A	25-10-1999 14-10-1999
US 6073018 A	06-06-2000	AU 1722199 A WO 9930518 A	28-06-1999 17-06-1999

NOTES TO FORM PCT/ISA/220 (continued)

The letter must indicate the differences between the claims as filed and the claims as amended. It must, in particular, indicate, in connection with each claim appearing in the international application (it being understood that identical indications concerning several claims may be grouped), whether

- (i) the claim is unchanged;
- (ii) the claim is cancelled;
- (iii) the claim is new;
- (iv) the claim replaces one or more claims as filed;
- (v) the claim is the result of the division of a claim as filed.

The following examples illustrate the manner in which amendments must be explained in the accompanying letter:

1. [Where originally there were 48 claims and after amendment of some claims there are 51]:
"Claims 1 to 29, 31, 32, 34, 35, 37 to 48 replaced by amended claims bearing the same numbers; claims 30, 33 and 36 unchanged; new claims 49 to 51 added."
2. [Where originally there were 15 claims and after amendment of all claims there are 11]:
"Claims 1 to 15 replaced by amended claims 1 to 11."
3. [Where originally there were 14 claims and the amendments consist in cancelling some claims and in adding new claims]:
"Claims 1 to 6 and 14 unchanged; claims 7 to 13 cancelled; new claims 15, 16 and 17 added." or
"Claims 7 to 13 cancelled; new claims 15, 16 and 17 added; all other claims unchanged."
4. [Where various kinds of amendments are made]:
"Claims 1-10 unchanged; claims 11 to 13, 18 and 19 cancelled; claims 14, 15 and 16 replaced by amended claim 14; claim 17 subdivided into amended claims 15, 16 and 17; new claims 20 and 21 added."

"Statement under article 19(1)" (Rule 46.4)

The amendments may be accompanied by a statement explaining the amendments and indicating any impact that such amendments might have on the description and the drawings (which cannot be amended under Article 19(1)).

The statement will be published with the international application and the amended claims.

It must be in the language in which the international application is to be published.

It must be brief, not exceeding 500 words if in English or if translated into English.

It should not be confused with and does not replace the letter indicating the differences between the claims as filed and as amended. It must be filed on a separate sheet and must be identified as such by a heading, preferably by using the words "Statement under Article 19(1)."

It may not contain any disparaging comments on the international search report or the relevance of citations contained in that report. Reference to citations, relevant to a given claim, contained in the international search report may be made only in connection with an amendment of that claim.

Consequence if a demand for international preliminary examination has already been filed

If, at the time of filing any amendments under Article 19, a demand for international preliminary examination has already been submitted, the applicant must preferably, at the same time of filing the amendments with the International Bureau, also file a copy of such amendments with the International Preliminary Examining Authority (see Rule 62.2(a), first sentence).

Consequence with regard to translation of the international application for entry into the national phase

The applicant's attention is drawn to the fact that, where upon entry into the national phase, a translation of the claims as amended under Article 19 may have to be furnished to the designated/elected Offices, instead of, or in addition to, the translation of the claims as filed.

For further details on the requirements of each designated/elected Office, see Volume II of the PCT Applicant's Guide.

NOTES TO FORM PCT/ISA/220

These Notes are intended to give the basic instructions concerning the filing of amendments under article 19. The Notes are based on the requirements of the Patent Cooperation Treaty, the Regulations and the Administrative Instructions under that Treaty. In case of discrepancy between these Notes and those requirements, the latter are applicable. For more detailed information, see also the PCT Applicant's Guide, a publication of WIPO.

In these Notes, "Article", "Rule", and "Section" refer to the provisions of the PCT, the PCT Regulations and the PCT Administrative Instructions respectively.

INSTRUCTIONS CONCERNING AMENDMENTS UNDER ARTICLE 19

The applicant has, after having received the international search report, one opportunity to amend the claims of the international application. It should however be emphasized that, since all parts of the international application (claims, description and drawings) may be amended during the international preliminary examination procedure, there is usually no need to file amendments of the claims under Article 19 except where, e.g. the applicant wants the latter to be published for the purposes of provisional protection or has another reason for amending the claims before international publication. Furthermore, it should be emphasized that provisional protection is available in some States only.

What parts of the international application may be amended?

Under Article 19, only the claims may be amended.

During the international phase, the claims may also be amended (or further amended) under Article 34 before the International Preliminary Examining Authority. The description and drawings may only be amended under Article 34 before the International Examining Authority.

Upon entry into the national phase, all parts of the international application may be amended under Article 28 or, where applicable, Article 41.

When?

Within 2 months from the date of transmittal of the international search report or 16 months from the priority date, whichever time limit expires later. It should be noted, however, that the amendments will be considered as having been received on time if they are received by the International Bureau after the expiration of the applicable time limit but before the completion of the technical preparations for international publication (Rule 46.1).

Where not to file the amendments?

The amendments may only be filed with the International Bureau and not with the receiving Office or the International Searching Authority (Rule 46.2).

Where a demand for international preliminary examination has been/is filed, see below.

How?

Either by cancelling one or more entire claims, by adding one or more new claims or by amending the text of one or more of the claims as filed.

A replacement sheet must be submitted for each sheet of the claims which, on account of an amendment or amendments, differs from the sheet originally filed.

All the claims appearing on a replacement sheet must be numbered in Arabic numerals. Where a claim is cancelled, no renumbering of the other claims is required. In all cases where claims are renumbered, they must be renumbered consecutively (Administrative Instructions, Section 205(b)).

The amendments must be made in the language in which the international application is to be published.

What documents must/may accompany the amendments?

Letter (Section 205(b)):

The amendments must be submitted with a letter.


The letter will not be published with the international application and the amended claims. It should not be confused with the "Statement under Article 19(1)" (see below, under "Statement under Article 19(1)").

The letter must be in English or French, at the choice of the applicant. However, if the language of the international application is English, the letter must be in English; if the language of the international application is French, the letter must be in French.

091700690

PATENT COOPERATION TREATY

PCT



INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference PAT 99409aPC	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/IB00/00229	International filing date (day/month/year) 24/02/2000	Priority date (day/month/year) 24/02/1999
International Patent Classification (IPC) or national classification and IPC H04Q7/38		RECEIVED JUL 11 2001
Applicant NOKIA MOBILE PHONES LIMITED et al.		Technology Center 2100

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.



2. This REPORT consists of a total of 8 sheets, including this cover sheet.

- ☐ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☒ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☒ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand 21/09/2000	Date of completion of this report 01.06.2001
Name and mailing address of the international preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465	Authorized officer Frey, R Telephone No. +49 89 2399 7522 

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/IB00/00229

I. Basis of the report

1. With regard to the **elements** of the international application (*Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)*):

Description, pages:

1-72 as originally filed

Claims, No.:

1-41 as originally filed

Drawings, sheets:

1/24-24/24 as originally filed

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language: , which is:

- ☐ the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of a translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
- ☐ the claims, Nos.:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/IB00/00229

☐ the drawings, sheets:

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)

6. Additional observations, if necessary:

III. Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

1. The questions whether the claimed invention appears to be novel, to involve an inventive step (to be non-obvious), or to be industrially applicable have not been examined in respect of:

☐ the entire international application.

☒ claims Nos. 40-42.

because:

☐ the said international application, or the said claims Nos. relate to the following subject matter which does not require an international preliminary examination (*specify*):

☒ the description, claims or drawings (*indicate particular elements below*) or said claims Nos. are so unclear that no meaningful opinion could be formed (*specify*):
see separate sheet

☐ the claims, or said claims Nos. are so inadequately supported by the description that no meaningful opinion could be formed.

☐ no international search report has been established for the said claims Nos. .

2. A meaningful international preliminary examination cannot be carried out due to the failure of the nucleotide and/or amino acid sequence listing to comply with the standard provided for in Annex C of the Administrative Instructions:

☐ the written form has not been furnished or does not comply with the standard.

☐ the computer readable form has not been furnished or does not comply with the standard.

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims 2-5, 11, 13, 14, 20, 22-25, 31, 38

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/IB00/00229

	No:	Claims	1, 6-10, 12, 15-19, 21, 26-30, 32-37, 39
Inventive step (IS)	Yes:	Claims	
	No:	Claims	1-39
Industrial applicability (IA)	Yes:	Claims	1-39
	No:	Claims	

2. Citations and explanations
see separate sheet

VI. Certain documents cited

1. Certain published documents (Rule 70.10)

and / or

2. Non-written disclosures (Rule 70.9)

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:
see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:
see separate sheet

Re Item III

Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

Claims 40 to 42 contravene Rule 6.2(a) PCT and are so unclear (Art. 6 PCT) that no opinion with respect to the requirements of Article 33(1) PCT can be given.

Re Item V

Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents:

D1: WO 97 34437 A (TELEFONAKTIEBOLAGET L M ERICSSON) 18
September 1997 (1997-09-18)

D2: WO 98 58475 A (TOSHIBA K K) 23 December 1998 (1998-12-23)

2. The subject-matter of **claim 1** is not novel (Art. 33(1) PCT).

Document D1 discloses, according to all features of claim 1,
a switch for establishing a call between a terminal of an originating network and a terminal of a terminating network (the function of any switch),
which switch comprises
an input for receiving call identification information in a first format from the originating network;
reformatting means for reformatting received call identification information into a second format;
an output means for outputting the call identification information in the second format over the terminating network (see in particular page 7, lines 14- 16; interfaces A/B and C); and
connection means for completing a connection, suitable for the identified call, between the terminals (see in particular page 8, lines 2-7).

3. The subject-matter of independent **claims 21, 37 and 39** is equally not novel (Art. 33(1) PCT).

The subject-matter of claim 39 corresponds substantially to that of claim 1. The subject-matter of claims 21 and 37 corresponds substantially to that of claim 1 drafted as a method.

4. Dependent **claims 2 to 20, 22 to 36 and 38** do not contain any features which, in combination with the features of any claim to which they refer, meet the requirements of the PCT in respect of novelty and/or inventive step, the reasons being as follows.

The importance of call type information, telecommunications service information, bearer service information and selection of proper bearer (**claims 2 to 5 and 22 to 25**) in the context of interworking is known from document D2 (see in particular page 82, lines 11- 13 and page 83, lines 12- 14).

The additional features of **claims 6 to 10, 12 to 19, 26 to 30 and 32 to 36** are at least implicitly disclosed by D1 (PSTN: fixed, analogue, in-band signalling; GSM: MSC, wireless, digital, out band signalling; call from the PSTN to the GSM network possible; proximity between gateway and MSC, e.g. fig. 1: there is no reason why gateway and MSC shouldn't be co-located when circumstances make it desirable; this applies equally to the optional co-location of the transcoder).

The wireless network being a UMTS network (**claims 11 and 31**) is an obvious possibility.

Numbering plans, as such, are well known. The combination of a numbering plan with the reformatting according to **claims 20 and 38** comes within the scope of the customary practice followed by persons skilled in the art, especially as the advantages thus achieved can readily be foreseen.

Re Item VI

Certain documents cited

US-A-6 073 018 (SALLBERG K), published 6 June 2000 (2000-06-06), filed 11 Dec 1997 (1997-12-11), appears to be very relevant. In particular, this document discloses the mapping of signalling messages between a wireless communications system and a digital network in response to available and requested bearer services.

Re Item VII

Certain defects in the international application

1. The independent claims should have been drafted in the proper two-part "characterised" form recommended by Rule 6.3.(b),(i),(ii) PCT, having a preamble that correctly reflects the nearest prior art, presumably that represented by the above noted D1.
2. In order to meet the requirements of Rule 5.1.(a),(ii) PCT, the relevant prior art, i.e. the documents noted above, should have been acknowledged by reference and briefly discussed in the introductory part of the description.
3. The claims lack reference signs where features shown in the drawings are referred to, Rule 6.2.(b) PCT.
4. The general statement in the first paragraph of page 72 is unclear, and when used to interpret the claims renders them also unclear, contrary to Article 6 PCT.
5. The "incorporated by reference" statement on page 53 should be deleted, since the application should be self-contained and these documents clearly do not contain matter regarding essential features of the invention (see PCT-Guidelines for Preliminary Examination, PG-II, 4.17).
6. The application should, for reasons of conciseness (Art. 6 PCT), include only the minimum necessary number of independent claims. Considering the nature of the invention a single independent claim for each category would have been appropriate.

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/IB00/00229

R It m VIII

Certain observations on the international application

Claims 5, 20 and 38 are not clear (Art. 6 PCT).

1. In claim 5 the sentence "the reformatting means ... *negotiate[s]* the bearer of the terminating network to *match* that of the originating network" is unclear. For the purpose of this examination this has been understood as meaning that the reformatting means selects a suitable bearer.
2. In claim 20, line 4 the term "output" should have been replaced by "output means" so as to be consistent with the terminology of claim 1.
3. In claim 38, it is not clear to what supposedly previously defined features the "reformatting, transmitting and establishing steps" refer. Furthermore, in the last line, it should have been clarified that "the primary call information is different *from the call identification of the predetermined connection*".

PCT REQUEST

PAT 99409aPC

Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM

0	For receiving Office use only	
0-1	International Application No.	
0-2	International Filing Date	
0-3	Name of receiving Office and "PCT International Application"	
0-4	Form - PCT/RO/101 PCT Request Prepared using	PCT-EASY Version 2.90 (updated 15.12.1999)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	International Bureau of the World Intellectual Property Organization (RO/IB)
0-7	Applicant's or agent's file reference	PAT 99409aPC
I	Title of invention	TELECOMMUNICATION SERVICES IDENTIFICATION
II	Applicant	
II-1	This person is:	applicant only
II-2	Applicant for	all designated States except US
II-4	Name	NOKIA MOBILE PHONES
II-5	Address:	KEILALAHDENTIE 4 FIN-02150 ESPOO Finland
II-6	State of nationality	FI
II-7	State of residence	FI
II-8	Telephone No.	+358 24 3061
II-9	Facsimile No.	+358 24 3064 544
III-1	Applicant and/or inventor	
III-1-1	This person is:	applicant and inventor
III-1-2	Applicant for	US only
III-1-4	Name (LAST, First)	HONKO, Harri
III-1-5	Address:	Tuomiokirkonkatu 38 C 17 FIN-33100 Tampere Finland
III-1-6	State of nationality	FI
III-1-7	State of residence	FI

PCT REQUEST

PAT 99409aPC

Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM

III-2	Applicant and/or inventor	
III-2-1	This person is:	applicant and inventor
III-2-2	Applicant for	US only
III-2-4	Name (LAST, First)	HARMOVAARA, Matti
III-2-5	Address:	KELLONSOITTAJANKATU 15 b 4 FIN-20500 TURKU Finland
III-2-6	State of nationality	FI
III-2-7	State of residence	FI
IV-1	Agent or common representative; or address for correspondence The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent
IV-1-1	Name (LAST, First)	JEFFERY, Kendra
IV-1-2	Address:	NOKIA IPR DEPARTMENT Nokia House Summit Avenue Farnborough, Hampshire GU14 ONG United Kingdom
IV-1-3	Telephone No.	01252 865000
IV-1-4	Facsimile No.	01252 865080
IV-2	Additional agent(s)	additional agent(s) with same address as first named agent
IV-2-1	Name(s)	HIBBERT, Juliet; HAWS, Helen, Louise; HIGGIN, Paul; MUIR, Henry; FRAIN, Timothy
V	Designation of States	
V-1	Regional Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	AP: GH GM KE LS MW SD SL SZ TZ UG ZW and any other State which is a Contracting State of the Harare Protocol and of the PCT EA: AM AZ BY KG KZ MD RU TJ TM and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT EP: AT BE CH&LI CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE and any other State which is a Contracting State of the European Patent Convention and of the PCT OA: BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG and any other State which is a member State of OAPI and a Contracting State of the PCT

PCT REQUEST

PAT 99409aPC


Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM

V-2	National Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	AE AL AM AT AU AZ BA BB BG BR BY CA CH&LI CN CR CU CZ DE DK DM EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW	
V-5	Precautionary Designation Statement In addition to the designations made under items V-1, V-2 and V-3, the applicant also makes under Rule 4.9(b) all designations which would be permitted under the PCT except any designation(s) of the State(s) indicated under item V-6 below. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit.		
V-6	Exclusion(s) from precautionary designations	NONE	
VI-1	Priority claim of earlier national application		
VI-1-1	Filing date	24 March 1999 (24.03.1999)	
VI-1-2	Number	9906756.3	
VI-1-3	Country	GB	
VI-2	Priority claim of earlier national application		
VI-2-1	Filing date	19 April 1999 (19.04.1999)	
VI-2-2	Number	9908847.8	
VI-2-3	Country	GB	
VI-3	Priority claim of earlier national application		
VI-3-1	Filing date	24 February 1999 (24.02.1999)	
VI-3-2	Number	9904181.6	
VI-3-3	Country	GB	
VII-1	International Searching Authority Chosen	European Patent Office (EPO) (ISA/EP)	
VIII	Check list	number of sheets	electronic file(s) attached
VIII-1	Request	4	-
VIII-2	Description	72	-
VIII-3	Claims	6	-
VIII-4	Abstract	1	p99409apctab.txt
VIII-5	Drawings	24	-
VIII-7	TOTAL	107	
VIII-8	Accompanying items	paper document(s) attached	electronic file(s) attached
VIII-8	Fee calculation sheet	✓	-
VIII-16	PCT-EASY diskette	-	diskette
VIII-18	Figure of the drawings which should accompany the abstract	3	
VIII-19	Language of filing of the international application	English	

PCT REQUEST

PAT 99409aPC

Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM

IX-1	Signature of applicant or agent	
IX-1-1	Name (LAST, First)	JEFFERY, Kendra

FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported international application	
10-2	Drawings:	
10-2-1	Received	
10-2-2	Not received	
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application	
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)	
10-5	International Searching Authority	ISA/EP
10-6	Transmittal of search copy delayed until search fee is paid	

FOR INTERNATIONAL BUREAU USE ONLY

11-1	Date of receipt of the record copy by the International Bureau	
------	--	--

PCT (ANNEX - FEE CALCULATION SHEET)

PAT 99409aPC

Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM


(This sheet is not part of and does not count as a sheet of the international application)

0	For receiving Office use only	
0-1	International Application No.	
0-2	Date stamp of the receiving Office	
0-4	Form - PCT/RO/101 (Annex)	
0-4-1	PCT Fee Calculation Sheet Prepared using	PCT-EASY Version 2.90 (updated 15.12.1999)
0-9	Applicant's or agent's file reference	PAT 99409aPC
2	Applicant	NOKIA MOBILE PHONES, et al.
12	Calculation of prescribed fees	fee amount/multiplier total amounts (CHF)
12-1	Transmittal fee T	⇒ 300
12-2	Search fee S	⇒ 1,530
12-3	International fee	
	Basic fee (first 30 sheets) b1	650
12-4	Remaining sheets	77
12-5	Additional amount (X)	15
12-6	Total additional amount b2	1,155
12-7	b1 + b2 = B	1,805
12-8	Designation fees	
	Number of designations contained in international application	83
12-9	Number of designation fees payable (maximum 8)	8
12-10	Amount of designation fee (X)	140
12-11	Total designation fees D	1,120
12-12	PCT-EASY fee reduction R	-200
12-13	Total International fee (B+D-R) I	⇒ 2,725
12-17	TOTAL FEES PAYABLE (T+S+I+P)	⇒ 4,555
12-19	Mode of payment	authorization to charge deposit account
12-20	Deposit account instructions The receiving Office:	International Bureau of the World Intellectual Property Organization (RO/IB)
12-20-1	is hereby authorized to charge the total fees indicated above to my deposit account	✓
12-20-2	is hereby authorized to charge any deficiency or credit any over-payment in the total fees indicated above to my deposit account	✓
12-21	Deposit account No.	25349
12-22	Date	24 February 2000 (24.02.2000)

PCT (ANNEX - FEE CALCULATION SHEET)

PAT 99409aPC

Original (for SUBMISSION) - printed on 24.02.2000 12:16:41 PM

12-23	Name and signature	JEFFERY, Kendra 
-------	--------------------	---

VALIDATION LOG AND REMARKS


13-2-6	Validation messages Contents	Yellow! The power of attorney or a copy of the general power of attorney will need to be furnished unless all applicants sign the request form.
		Green? Priority 1. The priority document is not enclosed. (The applicant must furnish it within 16 months from the earliest priority date claimed)
		Green? Priority 2. The priority document is not enclosed. (The applicant must furnish it within 16 months from the earliest priority date claimed)
		Green? Priority 3. The priority document is not enclosed. (The applicant must furnish it within 16 months from the earliest priority date claimed)
13-2-8	Validation messages Payment	Green? Please ensure that you have a valid deposit account with the receiving Office selected.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : H04Q 7/38, 11/04, 3/72		A1	(11) International Publication Number: WO 00/51387
			(43) International Publication Date: 31 August 2000 (31.08.00)
(21) International Application Number: PCT/IB00/00229 (22) International Filing Date: 24 February 2000 (24.02.00) (30) Priority Data: 9904181.6 24 February 1999 (24.02.99) GB 9906756.3 24 March 1999 (24.03.99) GB 9908847.8 19 April 1999 (19.04.99) GB (71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LIMITED [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI). (72) Inventors; and (75) Inventors/Applicants (for US only): HONKO, Harri [FI/FI]; Tuomiokirkonkatu 38 C 17, FIN-33100 Tampere (FI). HARMOVAARA, Matti [FI/FI]; Kellonsoittajankatu 15 b 4, FIN-20500 Turku (FI). (74) Agents: JEFFERY, Kendra et al.; Nokia IPR Department, Nokia House, Summit Avenue, Farnborough, Hampshire GU14 0NG (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: TELECOMMUNICATION SERVICES IDENTIFICATION IN A GATEWAY



(57) Abstract

A method and apparatus are disclosed for identifying telecommunications services. The apparatus enables call establishment between a terminal of an originating analogue network and a terminal of a digital terminating network. It comprises an input for receiving call identification information in a first format from the originating network, means for reformatting received call identification information into a second format, output means for outputting the call identification information in the second format over the terminating network; and connection means for completing an appropriate connection between the terminals.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TELECOMMUNICATION SERVICES IDENTIFICATION IN A GATEWAY**Telecommunication Services Identification****Field of the Invention**

The present invention relates to a method and apparatus for identifying the type of telecommunications service required during call establishment over two networks. In particular, it relates to a method and apparatus for establishing call control appropriate to the telecommunications service, and more specifically to the service identified by the originating network.

Background of the Invention

Today, transmission of information via communications networks is commonplace. There is ever increasing demand for more rapid and flexible data exchange and the nature of the data to be transmitted is becoming ever more varied. Communications networks are also very diverse in scale and nature, from local area networks (LANs) comprising a handful of personal computers within a small company, to the Internet, providing the possibility for data exchange at a global level.

Communications networks have different characteristics and operating principles. Some are designed specifically for telecommunications and others are intended for more diverse data communications. Many different network architectures are employed, and a wide variety of data communication protocols are used to transmit information. Some networks, for example parts of the traditional Public Switched Telephone Network (PSTN) still utilise analogue data transmission techniques, while others, for example the Integrated Services Digital Network (ISDN) and the Public Land Mobile Network (PLMN), of which the GSM mobile telephone network is an example, employ digital communication technology.

Networks specifically designed for telecommunications still commonly use circuit switched data communication, in which specific network resources are allocated to establish and maintain a connection between end users of the network. Other networks, more typically, those designed primarily for general-purpose data communications, such as the Internet and local area networks, use packet switched communications protocols in which no dedicated physical connection must be established or maintained. In this kind of network, the continuous flow of data to be transmitted is divided into packets, each of which is routed, often in an independent connectionless manner, between the end users of the network.

In the traditional telecommunications sector, there is considerable interest in diversification and the provision of new telecommunications and datacomms services for network subscribers. In the data communications sector there is also increased interest in the provision of more telecomms oriented services. Thus, progressive overlap (or convergence) between the roles of telecommunications and data communications networks is occurring.

This convergence has given rise to a greater need to transfer data between dissimilar communications networks. However, because of the inherently diverse nature of currently existing telecommunications and data communications networks, a significant problem of inter-operability or interworking exists.

The problem of establishing communication between dissimilar networks will now be considered in greater detail. Throughout the following discussion and the description of the invention presented later in this document, the following interworking scenarios will be considered in detail:

- a) interworking between the Public Switched Telephone Network (PSTN) and the Public Land Mobile Network (PLMN) and
- b) interworking between the Integrated Services Digital Network (ISDN) and the Public Land Mobile Network (PLMN).

Furthermore, particular reference will be made to the provision of circuit switched telecommunications services between PSTN and PLMN networks as well as between the ISDN and PLMN networks. It should be noted that in the following, the term PSTN refers to a purely analogue land-line telephone network, while the terms ISDN and PLMN refer to networks employing entirely digital communications technology. However, although the ISDN and PLMN networks are both considered as purely digital in nature, it should be noted that in certain situations end-to-end digital communication between ISDN and PLMN networks may not be possible. This situation may arise, for example due to the characteristics of intervening connecting network elements. Thus, special consideration will also be given to ISDN - PLMN interworking issues.

When setting up a circuit switched connection for a telecommunications service, an appropriate bearer service must be established. A bearer service is a type of telecommunications service that provides the capability for the transmission of signals between user-network interfaces [Ref. ITU-T I.112]. In order for circuit switched communication to take place between two dissimilar networks, an end-to-end connection must be established. This requires an appropriate bearer service to be set up and maintained between each user's terminal equipment and its respective network interface. If the networks in question employ different communication protocols, as is generally the case, protocol conversion is also required to enable end-to-end communication.

The type of bearer service to be established depends on the type of telecommunications service required by the end users. For example, in some situations it may be necessary to establish a bearer service appropriate for a conventional speech telephone call, while in other cases a bearer service suitable for fax or data communication may be required. When establishing communication between two dissimilar networks, end-to-end indication of the type of communication requested is desirable in order to enable selection of an appropriate bearer service in both networks. As data communications and signalling protocols are typically different in the two networks, the signalling of

requested call type information between the networks cannot be achieved in a straightforward manner. This is particularly true in situations where end-to-end digital communication cannot be effected, as is the case when interworking between the analogue Public Switched Telephone Network, where call type information is provided by in-band signalling and the Public Land Mobile Network, where call type information is indicated using digital out-band signalling.

Figure 1 illustrates the architecture of the GSM Public Land Mobile Network. As can be seen from Figure 1, the GSM architecture comprises a gateway mobile switching centre (MSC) 10 which interfaces with fixed networks such as the PSTN and / or ISDN 15 and a GSM radio network. The GSM radio network comprises base station systems comprising a base station controller 16 and base transceiver stations (BTS) 17. The BSS comprises a transcoder TC (e.g. for converting to GSM speech). In Figure 1, the TC 101 is shown in the BSC, but could alternatively be in another part of the BSS, such as a BTS 17. Mobile stations are coupled to the BTSs via an air interface. The gateway MSC is also connected to subscriber and terminal equipment databases in the form of a home location register (HLR) 12, visitor location register (VLR) 13, and equipment identity register (EIR) 14. The EIR contains information relating to the mobile terminals and the VLR provides a local store of all the information required to handle calls to and from mobile users in the location area relating to that particular VLR. The HLR 12 permanently stores all the user parameters of the mobile stations, including the subscriber numbers associated with a particular mobile station and their corresponding service type. Since the PSTN is an analogue network and the GSM PLMN is digital, they are not directly compatible. Hence, the gateway MSC 10 has an associated interworking function (IWF) 11, which is a functional entity enabling interworking between the PLMN and PSTN / ISDN. Typically, the interworking function comprises a modem or modem pool for interfacing with analogue PSTN networks.

In the example considered here, the interworking function IWF in the gateway MSC 10 acts as the network interface for both the PSTN / ISDN and the PLMN and provides the necessary protocol conversion to enable end-to-end communication.

Conventionally in PLMN systems, different telecommunication services have been identified by adopting a multiple numbering scheme, that is, by dedicating a specific subscriber number (MSISDN) to a specific telecommunications service. For example, in GSM, the subscriber may currently have assigned mobile terminated GSM speech, data and / or fax numbers depending upon his profile. As previously described, there is currently considerable interest in the provision of additional and more widely varied telecommunications services. In the future, it is proposed that mobile telephone subscribers will also have the option of further high-speed data and multimedia services which, too, will have dedicated subscriber numbers.

The provisions of the current GSM multiple numbering scheme are laid down in GSM technical specification 09.07. According to GSM 09.07, a subscriber is allocated a number of MSISDNs, each associated with a particular telecommunications service. Some interworking information (IWI) is linked with each of these numbers and stored in the subscriber's HLR. The contents of the interworking information is specified in GSM 03.08 and comprises either one or two complete BC (Bearer Capability) information elements, whose contents are specified by GSM recommendation 07.01 and which are coded as described in GSM recommendation 04.08 para 10.5.4.5.

Interworking between the PSTN and a PLMN will now be described in the context of the conventional multiple number scheme as set down in GSM 09.07 and with reference to Figure 2 of the appended drawings.

As illustrated in Figure 2, when a call originates from the PSTN 15 (in this example a data call), an initial SETUP message is sent which includes the

called line identification (CLI) [Step 1]. As described above, the HLR contains a database entry corresponding to this CLI indicating the call type. The MSC 10 asks the HLR 12 for the call type and bearer capability corresponding to the CLI, and sends a setup message to the MS 18 to inform it of the incoming call and of the call type [Step 2]. The MS 18 responds by sending a CALL-CONF message after having checked its compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. This message is forwarded as a CALL-PROC message to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and a connection appropriate for the data call is made.

Use of a multiple numbering scheme, such as that defined in GSM 09.07, eliminates the need for end-to-end signalling of call type and bearer capability information in situations where end-to-end digital communication cannot be effected. This feature of the multiple numbering scheme is particularly advantageous in mobile terminated calls that originate from a PSTN. Because the mobile subscriber is allocated a separate telephone number for each telecommunications service and appropriate interworking information is associated with each number, there is no need to transmit information about the call type and required bearer services across the boundary between the PSTN and the GSM network. This approach solves the problem of how to provide information about the required bearer service for data calls originating from the PSTN. The multiple numbering scheme may also simplify interworking with ISDN networks. Although end-to-end digital communication is in theory possible between PLMN and ISDN networks, it is sometimes not possible at all levels due to properties of the ISDN or other connecting networks.

It should be noted, however, that the multiple numbering scheme defined by GSM 09.07 also has significant disadvantages. It increases the complexity of numbers to be dialled, increases the amount of subscriber numbers in use and places a burden on the user who must remember which number corresponds to which telecommunications service. Additionally, the storage of information concerning bearer capability in the HLR increases the storage requirements of the HLR, which is undesirable, particularly in view of the likely increase in the number of available telecommunications services in the near future. Furthermore, under the multiple numbering scheme, optimisation of bearer services (e.g. data transfer rates) is not possible as no mechanism for end-to-end negotiation is provided. For example, when a PSTN originated, mobile terminated call is established, the bearer service for that telecommunications service is set up with reference to the interworking information (IWI) stored in the HLR and no end-to-end adjustment of bearer services is possible. A similar situation may occur when interworking between certain ISDN networks and the PLMN, particularly when end-to-end digital connection at all levels cannot be achieved. This may lead to non-optimal use of the available transmission bandwidth in certain situations, for example if the mobile subscriber roams to a PLMN network which has different bearer capabilities from his/her home network.

Embodiments of the present invention provide a mechanism which identifies and maps call identification information (e.g. call type and bearer capability information) between dissimilar networks. Such a mapping scheme can be used for example to: a) enable optimisation of bearers in a multiple numbering scheme; b) allow the use of a reduced numbering scheme; or c) enable implementation of a single numbering scheme. In order to enable use a single numbering scheme, in which calls of all types are directed to a single subscriber number, mapping of call identification information between dissimilar networks is needed. This is achieved in embodiments of the invention by enhancing the functionality of the interworking function between networks, enabling the reformatting of call type information and enhanced

transmission of bearer capability information between networks. The mapping of the call type information eliminates the need for the aforementioned multiple numbering scheme. It thus simplifies operability of the system from a user standpoint, as the caller only needs to remember one number for the party to be called. Also, it reduces the need to increase the length of subscriber numbers to cater for additional services subscribed to in the future. Furthermore, the processing strain on the HLR is reduced. Mapping the bearer services, on the other hand, provides the additional advantage of enabling the radio bearer to be optimised. That is, the radio bearer may be negotiated to match that of the PSTN / ISDN, thus optimising the bandwidth used by the wireless network.

According to one aspect of the present invention, there is provided a switch for establishing a call between a terminal of an originating network and a terminal of a terminating network, the switch comprising: an input for receiving call identification information in a first format from the originating network; means for reformatting received call identification information into a second format; an output means for outputting the call identification information in the second format over the terminating network; and connection means for completing a connection, suitable for the identified call between the terminals.

This switch enables the elimination and / or reduction of the use of the aforementioned multinumbering scheme.

The call identification information may comprise call type information and/or bearer information.

The call type information may, for example, relate to telecommunications service information (e.g. H.324, teleservice information).

The provision of bearer information enables the terminating network to use the same bitrate as is available on the originating side, thereby ensuring that bandwidth efficiency is optimised.

The terminating network is preferably a wireless communications network, such as an UMTS or GSM network.

Optionally the switch is an MSC or GMSC.

The switch may further comprise means, coupled to the input, for determining primary call type information on the basis of a subscriber number, for forwarding first primary call identification information to the output, and for forwarding further primary call identification information to the reformatting means. Such a switch may, for example, enable a dual numbering system to be adopted, to distinguish between calls of primary types "speech" and "data". In this case, all calls of "speech" primary type are preferably automatically connected, and further determination of actual data type is made of calls of "data" primary type.

According to another aspect of the present invention, there is provided method for establishing a call between a terminal of an originating network and a terminal of a terminating network, the method comprising: receiving call identification information in a first format from the originating network; reformatting received call identification information into a second format; outputting the call identification information in the second format over the terminating network; and completing a connection, suitable for the identified call, between the terminals.

According to a further aspect of the present invention, there is provided a method for establishing a call between a terminal of an originating network and a terminal of a terminating network, the method comprising: establishing a call of a predetermined type; transmitting call identification information in a

first format from the originating terminal to the terminating network; reformatting received call identification information into a second format; transmitting the call identification information in the second format to the terminating terminal; and establishing a connection, suitable for the identified call, between the terminals.

According to another aspect of the invention, there is provided a switching system for establishing a call from a terminal of an originating network and a terminal of a terminating network, the switching system comprising: means for receiving call identification information in a first format from the originating network; means for reformatting received call identification information into a second format; means for transmitting the call identification information in the second format over the terminating network; and connection means for completing a connection, suitable for the identified call, between the terminals.

According to an embodiment of the present invention an MSC is provided with a transcoder and interworking function. This is in contrast to conventional GSM systems for example, in which the transcoder forms part of the base station subsystem.

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings, of which:

- Figure 1 illustrates the current GSM PLMN and its connection to the PSTN / ISDN;
- Figure 2 illustrates data call establishment from a PSTN terminal to a mobile station using the conventional multiple numbering scheme;
- Figure 3 illustrates establishment of an H.324 transparent video call from a PSTN terminal to a mobile station using an enhanced multiple

numbering scheme according to a first embodiment of the invention;

- Figure 4 illustrates establishment of an H.324 transparent video call from a PSTN terminal to a mobile station using an enhanced multiple numbering scheme according to the first embodiment of the invention, illustrating involvement of the PSTN local exchange during call setup;
- Figure 5 illustrates identification of the telecommunications service required for a PSTN originating call by an MSC of the invention;
- Figure 6 illustrates establishment of a data call from a PSTN terminal to a mobile station using a single numbering scheme according to a second embodiment of the invention;
- Figure 7 illustrates establishment of a data call from a PSTN terminal to a mobile station using a single numbering scheme according to a second embodiment of the invention and shows the involvement of the PSTN local exchange;
- Figure 8 illustrates an alternative method of data call establishment from a PSTN terminal to a mobile station using a single numbering scheme according to the second embodiment of the invention;
- Figure 9 illustrates establishment of a data call from a mobile station to a PSTN terminal using V.8bis signalling according to the second embodiment of the invention;
- Figure 10 illustrates establishment of a data call from a mobile station to a PSTN terminal using V.8 signalling, according to the second embodiment of the invention;
- Figure 11 illustrates establishment of a data call from a mobile station to a PSTN terminal using V.8 signalling, according to a second embodiment of the invention and shows the involvement of the PSTN local exchange;
- Figure 12 illustrates establishment of a data call from an ISDN terminal to a UMTS mobile station according to the second embodiment of the invention using end-to-end digital communication;

- Figure 13 illustrates establishment of a data call from an ISDN terminal to a UMTS mobile station according to the second embodiment of the invention in a situation where end-to-end digital communication cannot be effected;
- Figure 14 illustrates establishment of a data call from a UMTS mobile station to an ISDN terminal according to the second embodiment of the invention using end-to-end digital communication;
- Figure 15 illustrates establishment of a data call from a UMTS mobile station to an ISDN terminal according to another embodiment of the invention in a situation where end-to-end digital communication cannot be effected;
- Figure 16 illustrates establishment of a data call from an ISDN terminal to a UMTS mobile station according to the second embodiment of the invention and shows the involvement of the ISDN local exchange;
- Figure 17 illustrates establishment of a data call from an ISDN terminal to a UMTS mobile station according to the second embodiment of the invention in a situation where end-to-end digital communication cannot be effected;
- Figure 18 illustrates establishment of a data call from a UMTS mobile station to an ISDN terminal according to the second embodiment of the invention and shows the involvement of the ISDN local exchange;
- Figure 19 illustrates establishment of a data call from a UMTS mobile station to an ISDN terminal according to the second embodiment of the invention in a situation where end-to-end digital communication cannot be effected;
- Figure 20 illustrates establishment of a data call between two UMTS mobile stations, according to the second embodiment of the invention;

- Figure 21 illustrates establishment of a data call between a UMTS mobile station and a 2nd generation GSM mobile station according to the second embodiment of the present invention.
- Figure 22 illustrates establishment of a data call from a PSTN terminal to a mobile station according to a third embodiment of the present invention;
- Figure 23 illustrates, in further detail, establishment of a data call from a PSTN terminal to a mobile station according to the third embodiment of the present invention; and
- Figure 24 illustrates typical mapping information for an H.324 call;

Detailed Description of the Invention

The invention concerns a method and apparatus for the control of different call types between incompatible networks, using unique call type differentiation. It is described with reference to the networks shown in Figure 1, namely the analogue PSTN network which uses in band signalling and the wireless digital GSM network which uses out band signalling. However, the invention is not restricted to call control over these networks, and is equally applicable to other non-directly compatible networks. One area in which the invention is proposed for use in the future is between a landline network (such as the PSTN or ISDN) and universal mobile telecommunication system (UMTS).

In the description of the embodiments of the invention presented later in the text, examples of call establishment between fixed line (PSTN / ISDN) and mobile (PLMN) multimedia terminals are presented. However, it should be appreciated that the invention is in no way limited to this exemplary application and may be applied, in principal, to any other kind of call establishment between dissimilar networks.

In the following, it is assumed that the fixed (PSTN / ISDN) and mobile (PLMN) multimedia terminals referred to in connection with exemplary embodiments of the invention are implemented according to ITU-T recommendations H.324, H.324/I (H.324 Annex D) or H.324/M (H.324 Annex C). The H.324 recommendations provide a framework for the implementation of multimedia terminals, permitting the communication of real-time video, audio or data, or any combination thereof. Multimedia terminals implemented according to H.324 may be stand-alone terminal equipment connected to a fixed-line PSTN / ISDN or may be mobile terminals for use in a PLMN. An H.324 multimedia terminal may also be implemented in a PC or computer workstation.

The basic H.324 recommendation sets down the requirements for a multimedia terminal designed for connection to a fixed line analogue telecommunications network, such as a PSTN telephone system. The H.324/I recommendation (H.324 Annex D) defines equivalent requirements for multimedia terminals connected to fixed line networks providing digital communication e.g. ISDN networks and H.324/M (H.324 Annex C) provides certain modifications to H.324, specifically designed to improve the robustness of the multimedia bit-stream to data transmission errors. These modifications have greatest effect on the H.223 multiplexing protocol. The suffix "M" for "mobile" is used to denote the fact that the H.324/M variant of H.324 is especially suitable for use in mobile applications, where transmission of multimedia data takes place over particularly error-prone communication channels. However, it should be noted that the use of recommendation H.324/M is not limited to mobile multimedia applications and may also be used in fixed-line networks. The differences between H.324 and H.324/M are described in Annex C of the H.324 recommendation.

While the reader is referred to the H.324, H.324/I and H.324/M recommendations for further details concerning the implementation of multimedia terminals, a brief outline of the functional elements of H.324,

H.324/I and H.324/M multimedia terminals is presented here to aid understanding of the invention.

The basic functional elements of an H.324 terminal intended for connection to an analogue PSTN are:

- a) A video codec implemented according to ITU-T recommendation H.261 or H.263;
- b) An audio codec according to recommendation G.723.1;
- c) Data protocols to support data applications such as electronic whiteboards, still image transfer, file exchange, database access, audiographics conferencing, remote device control, network protocols etc. According to H.324 all data protocols are optional, but may include:
 - i) T.120 point-to-point and multi-point teleconferencing;
 - ii) T.84 point-to-point still image transfer;
 - iii) T.434 point-to-point file transfer;
 - iv) H.224 / H.281 far-end camera control;
 - v) T.30 facsimile transfer;
 - vi) T.140 text conversation protocol;
- d) A control protocol according to ITU-T recommendation H.245, providing signalling to enable correct end-to-end operation of the multimedia terminal;
- e) A multiplexing protocol according to H.223, for multiplexing video, audio data and control information into a single bit-stream for transmission and for demultiplexing received multimedia bit-streams; and
- f) A modem, conforming to recommendations V.34 and V.8 (and optionally V.8bis).

The V.34 / V.8 / V.8bis compliant modem of an H.324 multimedia terminal is an essential element, enabling the terminal to provide an analogue output for transmission to the PSTN and enabling the conversion of analogue signals

received from the PSTN into a digital bit-stream for further processing and / or reproduction within the terminal. However, the modem may be implemented as an external unit, in which case it is connected as an interface between the multimedia terminal and the PSTN and its operation is controlled by the multimedia terminal according to recommendation V.250 (ex V.25ter).

When setting up e.g. a video call between two H.324 multimedia terminals, connected via a PSTN telephone network, the calling terminal initiates a call start-up procedure. The calling terminal first requests a connection according to the standard procedures for analogue (voice) telephony. Upon successful setup of a conventional analogue (voice) connection, the H.324 terminal enters a V.8 start-up procedure. The calling terminal transmits a CI (Call Indication) calling tone in which it signals the "H.324" V.8 CF (Call Function) which, according to the V.8 recommendation has a value 0x21. The CF information element identifies the call type required by the calling terminal. If the calling terminal subsequently detects a response from a V.34 compliant modem at the receiving end, the start-up procedure for that modem is followed. It should be noted that if both the calling and called multimedia terminals support V.8bis, the users have the opportunity to speak before proceeding to multimedia telephony.

At the end of the V.34 modem setup and handshaking procedure, a data connection is effectively established between the two multimedia terminals. Following this, system-to-system communication is initiated using the H.245 control protocol and logical channels are opened for the various information streams to be transferred.

The data rates used in end-to-end communication are defined in the V.34 recommendation and range from 2400 bits/s to 33600 bits/s. Support of the two highest data rates, 31200 bits/s and 33600 bits/s, is optional, the highest rate for which support is mandatory being 28800 bits/s. In multimedia (e.g. video) communications, higher data rates are preferred due to the large data

throughput required for real-time video. Thus, data rates of 28800 bits/s and above are considered the most appropriate for use in video telephony applications.

In an H.324/I terminal, intended for direct connection to a fixed-line digital network such as an ISDN, the V.8 / V.8bis / V.34 modem is replaced with a I.400-series ISDN user-network interface. Call setup between two H.324/I compliant multimedia terminals connected via an ISDN network is generally performed according to recommendation V.140. Call setup according to V.140 has three phases. In phase 1, the calling terminal transmits a repeating characteristic 80-bit pattern to indicate to the called terminal that it supports V.140. If a characteristic V.140 bit pattern is also detected in received data, this indicates that the called terminal supports V.140 and call setup can proceed. If no V.140 response is received after a certain predefined time-out interval, the calling terminal may fall back to any other non-V.140 protocols it supports, for example V.8 or V.8bis. In order to enable fall-back to V.8 or V.8bis, the calling terminal also transmits V.8 / V.8bis messages coded as digital audio (according to recommendation G.711) and listens for corresponding digitally encoded V.8 / V.8bis responses from the called terminal.

Assuming that a V.140 response is received during phase 1, phase 2 of the V.140 call setup procedure is entered. The calling terminal now determines the characteristics of the ISDN connection. A variety of ISDN networks are currently in use, including networks that provide communication at 56 kbits/s and 64 kbits/s. Thus, the nature of the end-to-end digital link, including data rate and bit alignment, must be confirmed before the link can be used for multimedia communication. Once the nature of the digital link has been established, phase 3 of the call setup procedure is entered. In this phase, the terminals exchange mode capabilities and select a mode. H.324/I specifies that the calling multimedia terminal provides call type information in BC (Bearer Capability) and LLC (Low Layer Compatibility) information elements.

These information elements are defined in ITU-T recommendation Q.931, which describes the protocol used in ISDN networks to establish, maintain and terminate network connections.

Once call setup using V.140 is complete, system-to-system communication between the terminals is initiated using the H.245 control protocol, just as in communication between H.324 terminals connected to a PSTN. The data rate used in end-to-end communication depends on the type of ISDN network connecting the two multimedia terminals. As stated above, ISDN networks providing data rates of 56 kbits/s and 64 kbits/s are currently in existence. Provisions are also laid down in recommendation V.110 which allow the use of lower data rates over ISDN networks. The data rates specified in V.110 correspond to many of rates used in communication between V.34 modems and are intended to provide compatibility between multimedia terminals connected to ISDN and PSTN networks.

In mobile a multimedia terminal implemented according to H.324/M (i.e. according to Annex C of H.324), the V.8 / V.34 modem is replaced with any appropriate wireless interface. H.324/M envisages that direct establishment of multimedia calls will be possible due the digital connection provided between terminals resident in PLMN networks. The data rates used for multimedia communication in future networks will be compatible with ITU-T recommendation V.110 and support will be provided for higher rates, such as 64 kbits/s.

As described above, multimedia terminals implemented according to recommendations H.324, H.324/I and H.324/M are adapted to employ different call setup procedures and provide their bearer capability information in different ways. Different data transfer rates and communications protocols are also used. Many of these differences arise from the characteristics and requirements of the networks in which the multimedia terminals are designed to operate.

The exemplary embodiments of the invention presented below describe a number of alternative procedures that enable improved call establishment between dissimilar networks, with particular emphasis on multimedia (video) telephony. These include embodiments that provide an enhanced multiple numbering scheme, embodiments that allow the use of a reduced numbering scheme and embodiments that enable implementation of a single numbering scheme. Some embodiments relate specifically to interworking between PSTN and PLMN networks, while others are related to interworking between ISDN and PLMN networks. In all cases, both mobile terminated and mobile originated call setup scenarios are described.

It is assumed throughout, that in order to enable comprehensive interworking between PSTN, ISDN and PLMN networks, the interworking function of the gateway MSC has a modem or modem pool providing compatibility with V.8, V.34, V.110, V.140 and optionally V.8bis. However, no limitation as to the functionality of the IWF should be implied.

It should also be noted that the basic principles of call type and bearer service identification and mapping, as well as the call setup procedures presented in the following embodiments of the invention, apply equally well to currently existing (2nd Generation) and future (3rd Generation) mobile networks. Throughout the text, the current GSM (Global System for Mobile Communications) is used as an example of a 2nd Generation PLMN network and the proposed UMTS (Universal Mobile Telephone System), currently undergoing standardisation, is used to exemplify a 3rd Generation PLMN.

In the example interworking scenarios described below, call setup signalling within the PLMN network (i.e. between the gateway MSC and the mobile terminal) is described with reference to standardised call setup messaging defined in GSM recommendation 04.08 para 9.3. Call setup signalling within the UMTS mobile network will be closely based on the provisions of GSM

04.08 and is defined in ITU-T recommendation 24.08. Therefore close correspondence between the two systems is assumed. Furthermore, call setup signalling within the ISDN network (i.e. between ISDN terminal equipment and ISDN local exchanges) takes place in an entirely analogous manner, as defined in ITU-T recommendation Q.931.

While the reader is referred to the appropriate ITU-T recommendations for details of GSM / UMTS and ISDN call setup signalling, a summary of some important features of call setup signalling according to GSM 04.08 (version 5.3.0) are provided here in order to aid understanding of the invention. Particular emphasis is given to the information content of signals exchanged between the network and the mobile station during call setup, both in the mobile terminated (MT) and mobile originated (MO) directions. More specifically, the function and information content of the SETUP and CALL-CONF (call confirmed) will be discussed. Analogous call setup messages are used in ISDN and UMTS networks and are defined in ITU-T recommendations 24.008 and Q.931, respectively.

SETUP

In mobile terminated (MT) call setup, a SETUP message is sent by the network (e.g. from an MSC) to the mobile station in order to initiate call establishment. In mobile originated (MO) call setup, call establishment is initiated when a SETUP message is sent from the mobile terminal to the network (GSM 04.08, paragraph 9.3.23). The SETUP message contains a number of information elements (IEs) that provide call routing and control information, as well as information about the nature of call to be established. Specifically, the SETUP message may contain up to two Bearer Capability (BC) information elements (referred to as Bearer Capability 1 and Bearer Capability 2), two Low Layer Compatibility (LLC) information elements and two High Layer Compatibility (HLC) IEs.

The purpose of the BC information element(s) is to describe a bearer service(s) for a call to be established and it is used for compatibility checking as described in GSM 04.08 Annex B. Details of the structure, contents and coding of the BC IE(s) are provided in GSM 04.08 paragraph 10.5.4.5.

According to GSM 04.08, paragraph 10.5.4.18, the purpose of the Low Layer Compatibility information element is to provide a means which should be used for compatibility checking by an addressed entity (e.g. a mobile terminal in an MT call). Details of the role played by LLC IEs in compatibility checking are presented in Annex B of GSM 04.08. As will be described later in the text, according to some embodiments of the invention, the LLC IE is chosen to contain information about a requested call type (e.g. an H.324 multimedia / video call). It should be noted that when a call is established between mobile terminals within a PLMN, the LLC information element is transmitted transparently from the calling party to the called party. However, when the calling party resides in another network, for example an ISDN, there is no guarantee that end-to-end transmission of LLC information elements is possible and thus end-to-end communication of call type information in LLC IEs is not assured. Therefore, the invention provides means for transmitting call type information between networks in situations where end-to-end communication of LLC information elements is not possible .

The High Layer Compatibility information element is also intended to provide a remote user with a means for compatibility checking. The content and coding of HLC IEs is described in GSM 04.08, paragraph 10.5.4.16 and its use in compatibility checking is presented in Annex B of that recommendation. According to some example embodiments of the invention described later in the text, HLC IEs are used to contain information about a requested call type. However, as was the case for LLC IEs, while High Layer Compatibility information elements are transmitted transparently between originating and terminating parties within a PLMN, end-to-end transmission of HLC IEs between dissimilar networks cannot be guaranteed. Thus, in those

embodiments of the invention where call type information is provided in HLC information elements, means are also provided to ensure that call type information can be communicated in situations where end-to-end transmission of HLC IEs is not possible.

CALL-CONF

According to GSM 04.08, paragraph 9.3.2, a CALL-CONF (Call Confirmed) message is sent by a called mobile station as a reply to the network in order to confirm an incoming call request. Like the SETUP message, the CALL-CONF message contains a number of information elements. Specifically, it may contain up to two Bearer Capability (BC) information elements. However, BC IEs are only included in the CALL-CONF message under certain conditions. In the context of the invention, the situations in which bearer capability information is included in a CALL-CONF message are a) when the mobile station wishes a bearer service to be established other than that indicated in the Bearer Capability 1 information element of an incoming SETUP message or b) when the Bearer Capability 1 information element received in connection with an incoming SETUP message is missing (e.g. empty) or not fully specified. Examples of the use of bearer capability information in CALL-CONF messages when interworking between dissimilar networks are presented in the exemplary embodiments of the invention which follow.

Establishment of a video call from a PSTN multimedia terminal to a mobile multimedia terminal (mobile terminated call) according to a first embodiment of the invention will now be described. The first embodiment of the invention relates to implementation of an enhanced multiple numbering scheme and will be described in the context of video call establishment from a PSTN multimedia terminal to a mobile multimedia terminal, as illustrated in Figures 3 and 4.

Figure 3 illustrates an example of video call establishment from a PSTN terminal to a mobile station using an enhanced multiple numbering plan.

The called party bearer capability information related to the called subscriber number is retrieved from the HLR. After reaching the connect phase [Step 8], the IWF modem starts listening to the CI (Call Indication) messages and proceeds to handshake with the modem of the originating end [Step 9]. As previously described, a standard compliant PSTN H.324 application will send the V.8 CF code 0x21 [Step 10]. Only after detecting the validity of incoming V.8 code does the MSC know that originating end is requesting a H.324 service and is not, for example a misdialled speech call to the called party's dedicated H.324 video service number.

Figure 4 illustrates the same embodiment of the invention as described in connection with Figure 3, showing the role played by the PSTN local exchange (LE) in call setup. The term local exchange is used to denote e.g. the telephone exchange with which the PSTN multimedia terminal is connected. Call setup signalling between exchanges within the PSTN network and between PSTN exchanges and (gateway) MSCs of the PLMN network takes place via a signalling network known as Signalling System Number 7 (SS7), the properties and implementation of which are defined in the ITU-T Q.700 series of recommendations. Generally, signalling between ISDN networks and the PLMN also takes place via an SS7 network, as does intra-PLMN signalling, for example between MSCs. The call setup messages used in the SS7 signalling system are termed ISUP (ISDN User Part) messages. Definitions of the ISUP messages discussed in connection with embodiments of the present invention can be found in ITU-T recommendation Q.762.

Referring to Figure 4, establishment of a video call from a PSTN multimedia terminal according to the first embodiment of the invention commences when the PSTN local exchange (LE) issues an ISUP Initial Address Message (IAM) [Step 1]. The IAM initiates seizure of an outgoing circuit and transmits number

and other information relating to routing and handling of the call. In this embodiment of the invention, in which a multiple numbering scheme is used for mobile terminated calls, the number indicated by the IAM is the called party's video service number. When the IAM is received by the MSC 10, it retrieves the call type and bearer capability information for the number indicated from the HLR 12 and transmits that information in a SETUP message to the MS 18 [Step 2]. In this case, as illustrated in Figure 4, the call type and bearer capability information retrieved from the HLR is carried in the Bearer Capability 1 information element of the SETUP message.

The MS 18 responds by sending a CALL-CONF message to the MSC 10 after having checked its compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. This message is forwarded as an ISUP Address Complete Message (ACM) to the calling terminal's PSTN local exchange [Step 4]. The ACM informs the PSTN LE that all the address signals required for routing the call to the called party have been received. Next, the MS 18 sends an ALERT message to the MSC 10, informing it that ringing has started to the called subscriber [Step 5]. This information is passed back to the PSTN LE as an ISUP Call Progress Message (CPG) [Step 6] and the PSTN LE subsequently connects the ringing tone to the calling terminal. When the called subscriber answers the call, a CONNECT message is sent from the MS 18 to the MSC 10 [Step 7]. This is transmitted back to the PSTN LE as an ISUP Answer Message (ANM) [Step 8].

After reaching the connect phase [Step 8], the IWF modem starts listening [Step 9] for the V.8 CI (Call Indication) messages expected from an H.324 compliant PSTN multimedia terminal. If a V.8 CF code 0x21 is received from the calling terminal [Step 10], the IWF modem replies, indicating its compatibility with V.34. Subsequently a V.34 start-up and handshaking procedure is initiated [Step 11] and an appropriate bearer for end-to-end communication is finally selected. As previously described, the V.34 recommendation makes provisions for the use of a range of data rates from

2400 bits/s up to 33600 bits/s, of which the higher data rates are most appropriate for video telephony. In the present exemplary embodiment, a V.34 data rate of 28800 bits/s is chosen for communication in the PSTN link of the end-to-end connection. A corresponding V.110 bearer service is selected for communication in the PLMN (GSM) link of the end-to-end connection.

The enhanced multiple numbering scheme for mobile terminated calls according to the first embodiment of the invention provides the advantage that the bearer services selected for end-to-end communication are optimised through a process of negotiation in which the interworking function of the gateway MSC listens to and interprets signalling from the originating network.

In the following, a second embodiment of the invention that employs a single numbering scheme, in which mobile subscribers are allocated a single MSISDN, will be described. In order to enable implementation of a single numbering scheme in different connection scenarios (including those where end-to-end digital connection is not possible), the gateway MSC 10 is provided with additional functionality, as outlined in Figure 5. Generally, this functionality is provided by the IWF and optionally the transcoder TC. However, alternatively, it may be provided by other parts of the MSC and / or other switches in the network.

In PSTN originated, mobile terminated call setup, the signalling detector 41 (comprising the TC and IWF) firstly detects signalling from the PSTN [Step 301]. Then it interprets the in-band signalling messages relating to the telecommunication services and maps them into appropriate digital out-band signalling [Step 302]. After mapping, the MSC 10 provides the appropriate call setup messaging for the identified call type [Step 303] to the mobile terminal. Consequently, the mobile station 18 is informed of the call type and required bearer service and an appropriate call connection is affected. Typical mapping information for an H.324 call is shown in Figure 24, and further

information on the mapping process is provided under the heading "Mapping" later in the text.

In mobile originated, PSTN terminated call setup, the MSC 10 receives out-band digital signalling from the mobile terminal indicating the type of call to be established and the bearer service(s) required. The MSC then converts (maps) the call type and bearer service information received from the MS 18 into appropriate analogue in-band signalling that can be interpreted by the terminating PSTN terminal.

Similar operations are necessary when interworking between PLMN and ISDN networks. In this case, the IWF of the MSC is generally required to map call type and bearer service information between different out-band digital formats. However, as explained above, end-to-end digital connection between PLMN and certain ISDN networks may not be possible and thus in some cases it is necessary to transmit call type information to a terminating ISDN network in-band or to receive in-band signalling from an ISDN network. According to the invention, the gateway MSC is also provided with the functionality to perform call type and bearer service information mapping operations between the PLMN and ISDN.

It should be appreciated, that depending on the exact network configuration, a given gateway MSC may enable interworking between the PLMN and PSTN only, the PLMN and ISDN only, a combination of the two, or may also provide interworking with other networks. Therefore, no limitation as to the general functionality of such a gateway MSC should be implied from the following description of the invention. Furthermore, the use of specific information elements (e.g. bearer capability BC, High / Low Layer Compatibility HLC / LLC etc.) to indicate call type and bearer capability during call setup, as well as the choice of specific values for particular fields within those information elements should not be construed as limiting the scope of the invention. The underlying characteristics of the invention apply equally

well to situations in which different information elements, data fields and values are used.

Examples of call setup according to the second embodiment of the invention will first be described by considering interworking between PSTN and PLMN networks. Two alternative procedures for mobile terminated call establishment are described with reference to Figures 6, 7 and 8. Two alternatives for establishing mobile originated calls are then described with reference to Figures 8, 9 and 10.

Figure 6 illustrates call establishment from a PSTN terminal to a mobile station using a single numbering plan according to the second embodiment of the invention. As mentioned above, in this embodiment, the MSC 10 comprises both the IWF and TC. Also, it is adapted to conform at least with V.8, and preferably V.8bis, so that it can recognise a call type from the V.8 / V.8bis call function information category. In particular, the MSC's modem pool includes a modem, which conforms to V.34, so as to support V.8 and optionally V.8bis. This modem acts as a signalling detector 41 for detecting and interpreting V.8 / V.8bis signalling.

When a call originates from the PSTN 15 (in this example a multimedia call), an initial SETUP message is sent from the PSTN terminal to the MSC 10 [Step 1]. The MSC 10, in turn, sends a SETUP message to the MS 18 associated with the subscriber number dialled, using GSM / UMTS call control signalling [Step 2]. In the example illustrated in Figure 6, the SETUP message informs the MS 18 of the incoming call and of a default call type: in this case speech. The MS 18 responds by sending a CALL-CONF message, after having checked its compatibility with the requested bearer capability [Step 3]. This message is forwarded as a CALL-PROC message to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber

[Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and a default speech connection is made [Step 9], and appropriate speech transcoding is activated in the transcoder unit.

Upon connection, the V.8 / V.8bis signalling detector 41 of the MSC 10 interprets the PSTN originated V.8 / V.8bis signalling [Step 10]. The signalling related to the telecommunication services is mapped into corresponding GSM / UMTS signalling by the MSC 10. In this case the signalling detector 41 identifies the telecommunication service category as a multimedia (H.324) call and a 28.8kbps transparent bearer service category. In other cases, more than one bearer service may be selected: for example, one for images and one for data. If necessary, connections within the MSC (including activation of modems) are rearranged for example as in the GSM Phase 1 proposed "alternate speech and data" service. The GSM / UMTS speech bearer output to the mobile station speech channel is preferably blocked to prevent loudspeaker activation in the MS until the call type has been determined. However connection between the terminals is maintained.

Next, after successful detection of the signalling expected by the modem configuration, the modems at the MSC and in the PSTN start a handshaking process [Step 11] which results in connection with a commonly agreed data modulation rate.

Then, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth. The MSC instigates modification of the bearer using the GSM layer 3 call control protocol (GSM 04.08) and the MS 18 is informed of the requested call type and bearer [Step 12]. The MS returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 13]. The connection is now complete for multimedia communication between the PSTN terminal and MS 18. Communication takes place in 3.1 kHz (external to the PLMN) bearer

service using the category involving the IWF modem and optimised radio bearer [Step 14].

Figure 7 illustrates PSTN originated, mobile terminated call setup according to the second embodiment of the invention, showing the involvement of the PSTN local exchange (LE), again using the example of an H.324 multimedia call. Further examples relating to the exchange of bearer capability information between the MSC 10 and the MS18 are also provided.

Referring to Figure 7, establishment of an H.324 call from a PSTN multimedia terminal commences when the PSTN local exchange (LE), with which the calling multimedia terminal is connected, issues an ISUP Initial Address Message (IAM) [Step 1]. When the IAM is received by the MSC 10, it sends a SETUP message to the MS 18 associated with the dialled number using GSM / UMTS call control signalling [Step 2]. The SETUP message informs the MS 18 of the incoming call and, in this case, of a default call type: speech. Information concerning the requested bearer service for the default call type is indicated in the Bearer Capability (BC) information element.

The MS 18 responds by sending a CALL-CONF message to the MSC 10 after having checked its compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. Preferably, and as permitted by the provisions of GSM 04.08 para 9.3.2, the CALL-CONF message contains information relating to the call types and bearer services supported by the mobile station. The CALL-CONF message may contain one or two BC IEs and the order in which bearer capabilities are listed may indicate a preference for a particular choice of bearer service.

Having received the CALL-CONF message from the MS, the MSC issues an ISUP Address Complete Message (ACM) to the calling terminal's PSTN local exchange [Step 4]. The ACM informs the PSTN LE that all the address signals required for routing the call to the called party have been received.

Next, the MS 18 sends an ALERT message to the MSC 10, informing it that ringing has started to the called subscriber [Step 5]. This information is passed back to the PSTN LE as an ISUP Call Progress Message (CPG) [Step 6] and the PSTN LE subsequently connects the ringing tone to the calling terminal. When the called subscriber answers the call, a CONNECT message is sent from the MS 18 to the MSC 10 [Step 7]. This is transmitted back to the PSTN LE as an ISUP Answer Message (ANM) [Step 8], a default speech connection is made [Step 9] and appropriate speech transcoding is activated in the transcoder unit.

Upon connection, the V.8 / V.8bis signalling detector 41 of the MSC 10 starts listening for PSTN originated V.8 / V.8bis signalling [Step 10]. Any received V.8 / V.8bis signalling related to telecommunication services is mapped into corresponding GSM / UMTS signalling by the MSC 10. After successful detection of the V.8 / V.8bis signalling from the calling H.324 PSTN terminal, the modems at the MSC and in the PSTN terminal start a handshaking process [Step 11] which results in connection with a commonly agreed data modulation rate.

Next, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth. The MSC instigates modification of the bearer using the GSM layer 3 call control protocol (GSM 04.08 para 9.3.13) and the MS 18 is informed of the requested call type and bearer [Step 12]. The MS returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 13]. The connection is now complete for multimedia communication between the PSTN terminal and MS 18 [Step 14].

Figure 8 illustrates an alternative PSTN originated, mobile terminated call setup procedure according to the second embodiment of the invention. As in Figure 7, involvement of the PSTN local exchange in call setup signalling is also shown. According to the example of Figure 8, establishment of an H.324

multimedia call begins when the PSTN local exchange, with which the calling multimedia terminal is connected, issues an ISUP Initial Address Message (IAM) [Step 1]. When the IAM is received by the MSC 10, it sends a SETUP message to the MS 18 associated with the dialled number using GSM / UMTS call control signalling [Step 2]. The SETUP message informs the MS 18 of the incoming call, but unlike the example call setup procedure described in connection with Figures 6 and 7, no default call type is indicated to the mobile terminal. Instead, the bearer capability information element of the SETUP message is left empty. According to this alternative call setup procedure, receipt of a SETUP message containing no bearer capability information, informs the mobile terminal that the calling party resides outside the PLMN network and is not able to provide direct out-band digital signalling relating to the call type and bearer service required. The mobile station forms a CALL-CONF message and transmits it to the MSC [Step 3]. Preferably, both call type and bearer capability information is provided in the CALL-CONF message in a standardised manner in accordance with the provisions of GSM 04.08 para 9.3.2 (or equivalent UMTS recommendation). However, it should be appreciated that use of particular information elements and the exact manner in which the information is coded is not significant for application of the invention.

Having received the CALL-CONF message, the MSC issues an ISUP Address Complete Message (ACM) to the calling terminal's PSTN local exchange [Step 4]. Next, the MS 18 sends an ALERT message to the MSC 10, informing it that ringing has started to the called subscriber [Step 5]. This information is passed back to the PSTN LE as an ISUP Call Progress Message (CPG) [Step 6] and the PSTN LE subsequently connects the ringing tone to the calling terminal. When the called subscriber answers the call, a CONNECT message is sent from the MS 18 to the MSC 10 [Step 7]. This is transmitted back to the PSTN LE as an ISUP Answer Message (ANM) [Step 8].

At this point, the V.8 / V.8bis signalling detector 41 of the MSC 10 starts listening for PSTN originated in-band signalling that might indicate the call type and bearer service required by the calling terminal [Step 9]. Specifically, if the signalling detector receives a V.8 CF code 0x21, the signature of an H.324 standard compliant PSTN multimedia terminal, the IWF modem replies, indicating its compatibility with V.34. Subsequently a V.34 start-up and handshaking procedure is initiated [Step 10], which results in connection between the MSC IWF and the calling PSTN terminal with a commonly agreed data modulation rate. The bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth and the connection is completed for end-to-end multimedia communication [Step 11]. In the example described in Figure 8, a V.34 data rate of 28800 bits/s is chosen for communication in the PSTN link of the end-to-end connection and a corresponding V.110 bearer is selected for communication in the PLMN (GSM) link.

If no appropriate in-band signalling can be identified by the signalling detector 41, or the bearer capabilities of the PSTN and mobile terminal are not compatible, a speech connection is established, or alternatively, the call is terminated.

Figures 9, 10 and 11 illustrate two alternative examples of call establishment for a mobile originated, PSTN terminated multimedia call, according to the second embodiment of the invention. In the first alternative, it is assumed that a default speech call is first established and then modified to a multimedia call at some later time using V.8bis signalling generated in, and then transmitted in-band from the MSC to the PSTN multimedia terminal. In the second alternative mobile originated call setup scenario, a multimedia call is established directly using appropriate V.8 signalling, generated by the MSC and transmitted in-band to the receiving PSTN terminal. It should be appreciated that the first alternative requires both the MSC and the receiving PSTN multimedia terminal to have V.8bis functionality. If either one is not

compliant with V.8bis, mobile originated multimedia call setup proceeds according to the second alternative.

Figure 9 illustrates a first alternative method of call establishment from a GSM / UMTS mobile station to a PSTN terminal (mobile originated call) according to the second embodiment of the invention. In this alternative method, a default speech call is first established between the MS and the PSTN terminal. Then, at some later time, either at the instigation of the user, or automatically, appropriate V.8bis is sent to the PSTN terminal in order to effect the changeover from speech to multimedia call. This method of mobile originated multimedia call establishment therefore requires that the MSC 10 is adapted to conform with V.8bis, so that it can send and recognise a call type from the V.8bis call function information category. In particular, for PSTN interworking the MSC's modem pool includes a modem, which conforms to V.34, so as to support V.8bis. The modem-transcoder unit of MSC acts as a signalling source and detector 41 for detecting and interpreting V.8bis signalling.

Referring to Figure 9, when a call originates from the MS 18 (in this example a multimedia call), an initial SETUP message is sent from the MS 18 to the MSC10. In this example, it is assumed that the SETUP message includes a video service specific codepoint by default in both the bearer capability BC and HLC / LLC information elements [Step 1]. The MSC 10 interprets the requested service from the BC information element and sends a SETUP message to the PSTN terminal 15 [Step 2]. As will be described in further detail later in the text, in the situation where the called party resides within a digital call control domain (ISDN, other PLMN), the called terminal interprets the requested service from the peer-to-peer transmitted HLC / LLC information element. However, in the current case, where the receiving terminal resides in a PSTN, the SETUP message [Step 2] does not forward digital call control specific information to PSTN terminal 15 to indicate the requested bearer service. Instead, it merely indicates a default call type (e.g.

speech) using the BC element. The PSTN terminal responds by sending a CALL-CONF message, without indication of the expected bearer service [Step 3]. Receipt of a CALL-CONF message without indication of bearer capability information effectively informs the MSC that the called party resides in a PSTN network. A CALL-PROC message is forwarded to the mobile station 18 by the MSC 10 [Step 4]. Then the PSTN terminal sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the PSTN terminal to the MSC [Step 7] and then from the MSC to the MS 18 [Step 8] when the called subscriber answers and a default speech connection is made [Step 9].

At the time the mobile station wishes to start the transition to video call (immediately, or later at the wish of mobile station user), the DCE in signalling detector 41 is told by the PLMN to send appropriate V.8bis signalling (for example, as described in Intel's Videophone Ready Modem Handbook Revision 1.1 and the H.324 specification) towards the PSTN terminal 15 [Step 10]. When the appropriate signalling is interpreted at the PSTN terminal 15, it switches to the appropriate DTE-DCE mode and starts modem handshaking with the modem in MSC 10 [Step 11]. This results in establishment of a data connection between modems with a common data modulation.

Next, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth, and the MS 18 is informed of the requested call type [Step 12]. The MS also gets confirmation that it has received an acknowledgement for its original video call mode change request, and returns a message to the MSC to complete the UMTS bearer modification process [Step 13]. The connection is now complete for multimedia communication between the MS 18 and PSTN terminal [Step 14]. Communication takes place in 3,1 kHz (external to the

PLMN) bearer service category [Ref: GSM 2.02] involving a modem in the interworking function of MSC 10 and using the optimised radio bearer.

Figure 10 illustrates a second alternative method of call establishment from a GSM / UMTS mobile station 18 to a PSTN terminal (mobile originated call setup) according to the second embodiment of the invention. More particularly, it shows establishment of an MS originated video call with direct video initialisation using MSC-configured V.8 signalling which originates in a data mode enabled modem of the MSC 10. Here it is assumed that the interworking function of the MSC is adapted to conform with V.8, (but not V.8bis), so that it can send and recognise a call type from the V.8 call function information category. In particular, the MSC's modem pool includes a modem, which conforms to V.34, so as to support V.8. This modem acts as a signalling source and detector 41 for detecting and interpreting V.8 signalling.

Referring to Figure 10, when a call originates from the MS 18 (in this example a multimedia call), an initial SETUP message is sent from the MS 18 to the MSC 10 [Step 1]. In this case, as in the example illustrated in Figure 9, it is assumed that the SETUP message sent from the mobile station to the MSC includes a video service specific codepoint by default in both the bearer capability BC and HLC information elements.

Having received the SETUP message from the mobile station, the MSC 10, in turn, sends a SETUP message to the PSTN terminal 15 associated with the dialled subscriber number [Step 2]. The SETUP message informs the PSTN terminal 15 of the incoming call, but in this case no default call type is indicated. The PSTN terminal 15 responds by sending a CALL-CONF message [Step 3], which is forwarded as a CALL-PROC message to the mobile station 18 by the MSC 10 [Step 4]. Then, the PSTN terminal sends an ALERT message to the MSC, informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Next, a CONNECT message is sent from the

PSTN terminal 15 to the MSC [Step 7] and the MSC, in turn transmits a CONNECT message to the mobile station [Step 8].

At this point, the MSC instructs the signalling detector 41 to generate in-band signalling to identify the call type and bearer service required by the calling mobile station to the PSTN terminal. Thus, in the current example, the IWF modem starts generating V.8 CI (Call Indication) messages, including the 0x21 CF code expected from an H.324 compliant multimedia terminal [Step 9]. If the signalling detector 41 subsequently receives an appropriate reply from the PSTN, for example indicating that the called terminal incorporates a V.34 compatible modem, the IWF initiates a V.34 start-up and handshaking procedure, resulting in connection between the MSC and the PSTN with a mutually agreed data modulation rate. The bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth and the connection is completed for end-to-end communication [Step 10a]. In this case using a V.34 data modulation rate of 28.8 kbits/s is established in the PSTN link and a corresponding V.110 data rate is used in the PLMN (GSM) link.

In the event that the signalling detector does not receive a reply from the PSTN, indicating that it is in communication with a V.34 compliant modem then, advantageously, after a given time-out or retry period, the MSC instigates establishment of a speech call between the MS and PSTN terminal. An end-to-end speech connection is then established [Step 10b]. This provides the system with a "fall-back" capability, preventing call failure in situations where, for example, the called PSTN does not support the call type and / or bearer service requested by the calling PLMN terminal.

Figure 11 illustrates the same mobile originated, PSTN terminated call set up scenario as described in connection with Figure 10, showing the role played by the PSTN local exchange.

Call establishment between ISDN and PLMN terminals according to the second embodiment of the invention will now be described with reference to Figures 12 to 19, which cover a variety of call setup scenarios, including both mobile terminated and mobile originated calls.

Figures 12 to 15 describe call setup between ISDN and PLMN networks assuming that a video service specific codepoint is included by default in both the bearer capability BC and HLC information elements. Figures 12 and 13 illustrate call establishment from an ISDN multimedia terminal to a mobile multimedia terminal (mobile terminated call), while Figures 14 and 15 illustrate call establishment from a mobile multimedia terminal to an ISDN multimedia terminal (mobile originated call). Figures 13 and 15 illustrate how a multimedia call can be established between the ISDN and PLMN networks when end-to-end (peer-to-peer) out-band digital signalling cannot be effected.

Figures 16 to 19 describe call setup between ISDN and PLMN networks assuming that a video service specific codepoint is included by default in both the bearer capability BC and LLC information elements. Figures 16 and 17 illustrate call establishment from an ISDN multimedia terminal to a mobile multimedia terminal (mobile terminated call), while Figures 18 and 19 illustrate call establishment from a mobile multimedia terminal to an ISDN multimedia terminal (mobile originated call). Figures 17 and 19 illustrate how a multimedia call can be established between the ISDN and PLMN networks when end-to-end (peer-to-peer) out-band digital communication is not possible.

Each of the ISDN / PLMN call setup scenarios introduced above will now be considered in detail with reference to the figures.

Figure 12 illustrates mobile terminated digital domain call setup with peer-to-peer HLC assuming global acceptance of the HLC information element to indicate an H.324 call type and use of a single numbering scheme for mobile

terminated calls. When a multimedia call originates from an ISDN terminal, an initial SETUP message is sent to the gateway MSC 10 [Step 1]. The SETUP message includes the called line identification (CLI) and an indication of the requested call type / bearer service. In this example, it is assumed that the SETUP message includes a video service specific codepoint by default in both the bearer capability BC and HLC information elements and that the ISDN terminal requests a UDI (Unrestricted Digital Information) 64 kbits/s bearer service. Assuming that end-to-end transmission of the HLC information element is possible, the MSC 10 interprets and forwards the requested bearer service and HLC information elements in a SETUP message to the mobile station 18 [Step 2]. The mobile station responds by sending a CALL-CONF message to the MSC, after having checked its compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. If the mobile station cannot support the requested bearer service, it provides an indication of an alternative bearer service, for example a V.110 28.8 kbits/s bearer, in the CALL-CONF message. This message is forwarded as a CALL-PROC message to the ISDN terminal by the MSC 10 [Step 4]. Next, the MS sends an ALERT message to the MSC, informing it that ringing has started to the called subscriber [Step 5] and subsequently the MSC connects the ringing tone to the calling subscriber [Step 6]. In the case that the requested bearer service can be supported by the MS 18, a CONNECT message is sent from the MS to the MSC when the called subscriber answers [Step 7a]. The MSC then issues a CONNECT message to the ISDN terminal [Step 8a] and a connection according to the originally requested bearer is made [Step 9a]. If an alternative bearer was suggested by the mobile terminal in the CALL-CONF message, call connection proceeds as shown in Steps 7b, 8b and 9b, resulting in the establishment of an alternative bearer.

Figure 13 illustrates call establishment from an ISDN terminal 15 to a mobile station 18 using a single numbering scheme according to the second embodiment of the invention. As in the example of Figure 12, it is assumed that the initial SETUP message transmitted from the ISDN terminal includes a

video service specific codepoint by default in both the bearer capability BC and HLC information elements. However, in this case, it is further assumed that end-to-end digital communication is not possible. As explained earlier, networks exist which fail to send out-band signalling messages end-to-end, and thus in this embodiment, the transcoder in MSC 10 is adapted to conform with V.140 (the ISDN in-band signalling protocol comparable to V.8 / V.8bis used in PSTN networks), so that it can recognise a call type from the in-band transmitted V.140 information. In particular, the MSC's modem-transcoder 41, is adapted to detect V.140 signalling in the LSBs of 56 / 64 kbps PCM modulated data as explained in the V.140 specification. Thus, the modem-transcoder unit of MSC acts as a signalling detector 41 for detecting and interpreting V.140 signalling.

When a call originates from an ISDN terminal 15 (in this example a multimedia call), an initial SETUP message is sent from the ISDN terminal to the MSC 10 [Step 1]. The MSC 10, in turn, sends a SETUP message to the MS 18 associated with the subscriber number dialled using GSM / UMTS call control signalling [Step 2]. The SETUP message informs the MS 18 of the incoming call and of a default call type: in this case speech with 3,1 kHz bearer service category (GSM 02.02). The MS 18 responds by sending a CALL-CONF message after having checked the compatibility with the requested bearer capability [Step 3]. This message is forwarded as a CALL-PROC message to the ISDN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the ISDN [Step 8]. When the called subscriber answers and a default speech connection is made [Step 9], appropriate speech transcoding is activated in the transcoder unit.

Upon connection, the V.140 signalling detector 41 of the MSC 10 listens for and interprets ISDN originated V.140 signalling [Step 10]. The detected signalling related to the telecommunication services is mapped into corresponding GSM / UMTS signalling by the MSC 10. In this case, the detector 41 identifies the telecommunication service categories as a multimedia (H.324) call and a 64kbps transparent UDI bearer service category and the MSC instigates modification of the bearer using the layer 3 call control protocol.

Then, the bearer capability for the wireless network is set to be the same as that determined for the ISDN, and the MS 18 is informed of the requested call type in the BC information element [Step 11]. The MS returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 12]. The connection is now complete for UDI multimedia communication between the PSTN terminal and MS 18 [Step 13].

Figure 14 provides two examples of mobile originated, ISDN terminated call setup, assuming peer-to-peer digital communication. In other words, it is assumed that end-to-end digital communication is possible i.e. through the ISDN, PLMN and any intervening networks, for example an SS7 network linking the ISDN local exchange and the gateway MSC. In the first example, the mobile terminal requests a UDI bearer service of 64 kbits/s and in the second a V.110 / 28.8 kbits/s bearer service is requested. In both cases, it is assumed that the called terminal is compatible with the requested call type / bearer service.

Following the call setup scenario shown in Figure 14, when a multimedia call originates from a mobile terminal, an initial SETUP message is sent to the gateway MSC 10 [Step 1a / 1b]. The SETUP message includes the called line identification (CLI) and an indication of the requested call type / bearer service. Again, it is assumed that the SETUP message includes a video service specific codepoint by default in both the bearer capability BC and HLC

information elements. Assuming that end-to-end digital transmission of the information elements is possible, the MSC 10 interprets and forwards the requested call type and bearer service information in a SETUP message to the ISDN terminal [Step 2a / 2b]. The ISDN terminal responds by sending a CALL-CONF message to the MSC [Step 3a / 3b]. The MSC then issues a CALL-PROC message to the calling mobile station [Step 4a / 4b] to indicate that call setup is proceeding.

Next, the ISDN terminal sends an ALERT message to the MSC, informing it that ringing has started to the called subscriber [Step 5a / 5b] and subsequently the MSC connects the ringing tone to the calling subscriber [Step 6a / 6b]. Finally, a CONNECT message is sent from the ISDN terminal to the MSC when the called subscriber answers [Step 7a / 7b]. The MSC then issues a CONNECT message to the mobile station [Step 8a / 8a] and the requested bearer service is established for end-to-end communication [Step 9a / 9b].

Figure 15 illustrates call establishment from a mobile station to an ISDN terminal (mobile originated call) according to the second embodiment of the invention, in the situation that end-to-end communication of the HLC is not possible. In this embodiment, the transcoder in the MSC 10 is adapted to conform with V.140 so that it can indicate a call type as in-band transmitted V.140 information. In particular, the MSC's modem-transcoder 41 can indicate V.140 signalling in the LSBs of 56 / 64 kbps PCM modulated data, as explained in the V.140 specification. Thus, the modem-transcoder unit of MSC acts as a signalling source 41 for transmitting, detecting and interpreting V.140 signalling.

When a call originates from the MS 18, an initial SETUP message is sent which, in this example, includes the video service specific codepoint by default in both BC and HLC information elements [Step 1]. The MSC 10 interprets the requested service from the BC information element and in

optimal case the called party would reside within digital call control domain (ISDN, other PLMN) end terminal would interpret it from the peer-to-peer transmitted HLC information element. However, in a network environment which does not conform to ISUP, the SETUP message transmitted from the MSC [Step 2] does not forward the digital call control specific information to the ISDN terminal. The ISDN terminal responds by sending a CALL-CONF message [Step 3].

Thus, connection signalling is completed with knowledge by MSC 10 that the called party resides in either an ISDN or PSTN network [Steps 4 – 8]. As both H.324 speech call first and direct video service signalling could be anticipated from the MS 18, the default user data (in this case speech) is switched to pass through a transcoder-voice modem unit 41 of MSC10 [Step 9]. At the time the mobile station wishes to start transition to a video call (immediately or later at the wish of mobile station user), the transcoder in the signalling detector 41 is instructed by the PLMN to send appropriate V.140 (and / or simultaneous V.8bis signalling) as described in V.140 and Intel's Videophone Ready Modem Handbook & H.324 specification towards the ISDN terminal 15 [Step 10]. When the signalling is interpreted in the ISDN terminal, it switches to an appropriate UDI mode and activates the video application at its own end.

Next, the bearer capability for the wireless network is set to be the same as that determined for the ISDN, so as to optimise the bandwidth, and the MS 18 is informed of the requested call type within the BC information element [Step 11]. The MS also gets a confirmation that it has received an acknowledgement for its original video call mode change request. The MS 18 returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 12]. The connection is now complete for multimedia communication between the MS 18 and the ISDN terminal [Step 13]. Communication takes place in 64 kbps UDI bearer service category.

Figure 16 illustrates call establishment from an ISDN terminal to a mobile station (mobile terminated call) using a single numbering scheme according to the second embodiment of the invention and further shows the involvement of the ISDN local exchange (LE) in call setup. The example of Figure 16 once more illustrates establishment of a multimedia (video) call. In this case, it is assumed that call type information is provided by default in both the bearer capability BC and LLC information elements transmitted from the ISDN terminal to the gateway MSC in the initial call SETUP message. This is in contrast to the examples presented in Figures 12 to 15, where call type information was carried in the BC and HLC information elements. In Figure 16, it is further assumed that the ISDN and PLMN are such that the LLC information element may be communicated end-to-end between networks.

Call control signalling between the ISDN terminal and the ISDN local exchange with which it is connected is implemented according to ITU-T recommendation Q.931 which provides standardised signalling for call setup, maintenance and teardown in ISDN networks. The ISDN call control procedures defined in Q.931 are substantially similar to those used in GSM call control signalling. Furthermore, as in the case of interconnection between the PSTN and PLMN, ISDN local exchanges are generally connected to gateway MSCs of the PLMN network via an SS7 network, as defined in the ITU-T Q.700 series recommendations. Call control signalling between the ISDN local exchange and the gateway MSC is accomplished using ISUP (ISDN User Part) messaging as defined in ITU-T recommendation Q.762.

Call establishment from an ISDN terminal to a PLMN mobile terminal commences when the ISDN terminal issues a Q.931 SETUP message [Step 1]. In this example, it is assumed that a video service specific codepoint is included by default in both the bearer capability BC and LLC information elements of the SETUP message. When the Q.931 SETUP message is received by the ISDN local exchange, it issues an ISUP IAM (Initial Address Message) to the gateway MSC of the PLMN [Step 2]. As end-to-end digital

signalling via the ISDN, SS7 and PLMN network is assumed possible in this example, the MSC is able to receive direct out-band signalling indicating the contents of the LLC and BC information elements. The MSC interprets the information concerning the requested call type and bearer capability received in connection with the IAM message and converts it into a format appropriate for transmission in the PLMN, for example as a GSM SETUP message, according to GSM 04.08 para 9.3.23 [Step 3] or its UMTS equivalent. Meanwhile, the ISDN local exchange informs the calling terminal that call setup is progressing by issuing a Q.931 CALL-PROC message [Step 4].

On receipt of the SETUP message, the mobile station checks its compatibility with the requested call type and bearer capability and transmits a CALL-CONF message back to the MSC [Step 5]. The MSC subsequently issues an ISUP Address Complete Message (ACM) to the ISDN local exchange to indicate that all the address signals required for routing of the call to the called party have been received [Step 6]. Next, the mobile terminal sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 7]. This information is forwarded as an ISUP Call Progress Message (CPG) via the SS7 network to the ISDN local exchange [Step 8] which, in turn, sends a Q.931 ALERT message to the calling ISDN terminal and subsequently connects the ringing tone to the calling subscriber.

When the called subscriber answers, a CONNECT message is sent from the MS to the MSC and is forwarded as an ISUP Answer Message (ANM) to the ISDN local exchange. Finally, the ISDN local exchange sends a Q.931 CONNECT message to the calling subscriber and a connection suitable for the call in question is established. If the mobile station can support the call type and bearer originally requested by the calling ISDN terminal, the call connection phase proceeds as indicated by steps 10a, 11a, 12a and 13a, of Figure 16. In the example of Figure 16, the calling ISDN terminal initially requests a multimedia (video) call using a 64 kbits/s UDI bearer service. In the event that the mobile terminal cannot provide the required bearer service

(e.g. it does not support the required data rate), this becomes apparent to the MSC at step 5, when the MS replies to the initial SETUP message. As explained earlier, according to GSM 04.08 para 9.3.2, the mobile terminal can provide alternative bearer capability information in the CALL-CONF message. Final call connection then proceeds according to steps 10b, 11b, 12b and 13b, in this example resulting in the establishment of an V.110 28.8 kbits/s bearer for the end-to-end connection.

Figure 17 also illustrates call establishment from an ISDN terminal to a mobile station (mobile terminated call) using a single numbering scheme according to the second embodiment of the invention. As in the example of Figure 16, it is assumed that a video service specific codepoint is included by default in both the bearer capability BC and LLC information elements of the SETUP message. However, in this case, it is assumed that end-to-end digital out-band communication is not possible, for example due to properties of the intervening network. In order to enable call setup using the aforementioned single numbering scheme in this situation, the interworking function IWF of the gateway MSC is invoked during call setup. Specifically, the IWF is adapted to conform with V.140, so that it can recognise a call type from in-band transmitted V.140 information. In particular, the MSC's modem-transcoder 41, is adapted to detect V.140 signalling in the LSBs of 56 / 64 kbps PCM modulated data as explained in the V.140 specification. Thus, in this case, the modem-transcoder unit of MSC acts as a signalling detector 41 for detecting and interpreting V.140 signalling.

When a call originates from an ISDN terminal 15 (again, in this example a multimedia call), a Q.931 SETUP message is sent from the ISDN terminal to the MSC 10 [Step 1]. Information concerning the requested call type and bearer service is present in the BC and LLC information elements of the Q.931 SETUP message. The MSC 10 then sends a SETUP message to the MS 18 associated with the subscriber number dialled using GSM / UMTS call control signalling [Step 2]. The SETUP message informs the MS 18 of the

incoming call and of a default call type: in this case speech with 3,1 kHz bearer service category (GSM 02.02). The MS 18 responds by sending a CALL-CONF message after having checked the compatibility with the requested bearer capability [Step 3]. This message is forwarded as a CALL-PROC message to the ISDN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the ISDN [Step 8]. When the called subscriber answers and a default speech connection is made [Step 9], appropriate speech transcoding is activated in the transcoder unit.

Upon connection, the V.140 signalling detector 41 of the MSC 10 starts to listen for and interpret ISDN originated V.140 signalling [Step 10]. The detected signalling related to the telecommunication services is mapped into corresponding GSM / UMTS signalling by the MSC 10 and, in this embodiment, the MSC instigates modification of the bearer using the layer 3 call control protocol. In other words, the detector 41 identifies the telecommunication service categories as a multimedia (H.324) call and a 64kbps transparent UDI bearer service category.

Then, the bearer capability for the wireless network is set to be the same as that determined for the ISDN, and the MS 18 is informed of the requested call type in the BC information element [Step 11]. The MS returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 12]. The connection is now complete for UDI multimedia communication between the ISDN terminal and MS 18 [Step 13].

Figure 18 illustrates two examples of call establishment from a mobile station to an ISDN terminal (mobile originated call) according to the second embodiment of the invention. It also illustrates the involvement of the ISDN

local exchange in call setup, showing the signalling that occurs between the gateway MSC of the PLMN network and the ISDN LE. In this case, it is further assumed that end-to-end digital communication is possible i.e. through the PLMN, ISDN and any intervening networks, for example an SS7 network linking the gateway MSC of the PLMN and the ISDN local exchange.

As in all previous cases, specific reference is made to video call establishment between multimedia terminals resident in the two networks. In the first example, illustrated by Steps 1a to 13a in Figure 18, it is assumed that the calling mobile terminal (and the PLMN) is capable of supporting video telephony using a UDI bearer at a data rate of 64 kbits/s, corresponding to the maximum data rate available for communication in the ISDN network. This situation can be considered optimal, as the capabilities of the mobile station (and the PLMN) match those of the ISDN and the maximum data rate available in the system can be used for end-to-end communication. It is assumed that mobile stations designed for use in 3rd Generation PLMN networks such as the UMTS system will be capable of supporting this kind of bearer service.

In the second example of mobile originated call setup, represented by Steps 1b to 13b in Figure 18, it is assumed that the calling mobile station and / or the PLMN does not support a UDI bearer at a data rate of 64 kbits/s. Therefore, the MS requests a video call to be established using a bearer service with a lower data rate, in this case a V.110, 28.8 kbits/s bearer service. The data rate used for end-to-end communication is thus limited by the capabilities of the mobile station and / or PLMN. This situation might arise, for example when using a first generation multimedia mobile terminal in 2nd Generation PLMN networks offering data rates appropriate for video telephony.

As shown in Steps 1a to 13a of Figure 18, call establishment from a PLMN mobile station to an ISDN terminal commences when the PLMN terminal

issues a SETUP message [Step 1a], conforming with the recommendations of GSM 04.08 para 9.3.23 or its UMTS equivalent. In the example call setup scenarios depicted in Figure 18, it is assumed that a video service specific codepoint is included by default in both the bearer capability BC and LLC information elements of the SETUP message.

The SETUP message is received by the MSC of the PLMN, which subsequently sends an ISUP Initial Address Message (IAM) to the ISDN local exchange [Step 2a]. As end-to-end digital signalling via the PLMN, SS7 and ISDN network is assumed possible in this example, the ISDN LE receives direct out-band signalling indicating the contents of the LLC and BC information elements. It then transmits a Q.931 SETUP message to the called ISDN terminal, indicating the requested call type and bearer capability in the BC and LLC information elements of the SETUP message [Step 3a]. Meanwhile, the gateway MSC informs the calling mobile station that call setup is proceeding by issuing a CALL-PROC message [Step 4a].

On receipt of the SETUP message, the ISDN terminal checks its compatibility with the requested call type and bearer capability and transmits a Q.931 CALL-CONF message back to the ISDN local exchange [Step 5a]. The ISDN local exchange subsequently issues an ISUP Address Complete Message (ACM) to the MSC to indicate that all the address signals required for routing of the call to the called party have been received [Step 6a]. Next, the ISDN terminal sends an ALERT message to the ISDN local exchange, informing it that ringing has started to the called subscriber [Step 7a]. This information is forwarded as an ISUP Call Progress Message (CPG) via the SS7 network to the MSC [Step 8a] which, in turn, sends an ALERT message to the calling mobile station [Step 9a] and subsequently connects the ringing tone to the calling subscriber.

When the called subscriber answers, a Q.931 CONNECT message is sent from the ISDN terminal to the MSC [Step 10a] and is forwarded as an ISUP

Answer Message (ANM) to the MSC [Step 11a]. Finally, the MSC sends a CONNECT message to the calling subscriber [Step 12a] and a connection suitable for the call in question is established [13a], in this case a UDI bearer service with a data rate of 64 kbits/s.

In the alternative call setup scenario illustrated by Steps 1b to 13b in Figure 18, call establishment proceeds in a manner similar to that just described. In this case, however, the mobile station does not support the 64 kbits/s UDI bearer, but indicates its support for a V.110 28.8 kbits/s bearer service in the initial SETUP message.

Figure 19 illustrates call establishment from a mobile station to an ISDN terminal (mobile originated call setup) according to the second embodiment of the invention, in the situation that end-to-end communication of the LLC information element is not possible. In this embodiment, the transcoder in the MSC 10 is adapted to conform with V.140 so that it can indicate a call type as in-band transmitted V.140 information. In particular, the MSC's modem-transcoder 41 can indicate V.140 signalling in the LSBs of 56 / 64 kbps PCM modulated data, as explained in the V.140 specification. Thus, the modem-transcoder unit of MSC acts as a signalling source 41 for transmitting, detecting and interpreting V.140 signalling. In this case, call setup proceeds in a manner analogous to that described in connection with Figure 15.

Figures 20 and 21 illustrate mobile-to-mobile call setup scenarios according to the second embodiment of the invention, again using the establishment of a multimedia call as an example. Figure 20 describes call establishment between two UMTS mobile stations, and shows the ISUP call setup signalling that takes between MSCs within the PLMN network. Figure 21 illustrates call establishment between a UMTS mobile station and a 2nd generation (e.g. GSM) mobile station.

A third embodiment of the invention enabling the use of a reduced numbering plan will now be described. Figures 22 and 23 illustrate call establishment from a PSTN terminal to a mobile station using a dual numbering plan. This embodiment provides a hybrid arrangement in which only two numbers are used: one to identify speech calls and the other to identify data calls. As in the arrangement of Figure 2, the HLR 12 contains a database entry corresponding to the called line identification indicating the call type. However, in this embodiment, this database has only two entries: one indicating that the call type is speech and the other indicating that the call type is data. If the call type is speech, the PSTN originating signal is transcoded by the TC 101 of the MSC 10 and transmitted over the radio network. However, if it is data, the actual type is determined by the IWF 11 as described with reference to Figure 5 above.

Call establishment in this embodiment will now be described in more detail, with reference to Figures 22 and 23.

Figure 22 illustrates call establishment for a speech call. When a call originates from the PSTN 15, an initial SETUP message is sent which includes the called line identification (CLI) – in this case for a speech call. [Step 1]. As mentioned above, the HLR contains a database entry corresponding to this CLI indicating the call type as speech. The MSC 10 asks the HLR 12 for this call type (bearer capability) corresponding to the CLI, and sends a SETUP message to the MS 18 to inform it of the incoming call and that the call type is speech [Step 2]. The MS 18 responds by sending a CALL-CONF message after having checked the compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. This message is forwarded as a CALL-PROC message to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from

the MSC to the PSTN [Step 8] when the called subscriber answers and a connection appropriate for the speech call is made.

Figure 23 illustrates call establishment for a data call. When a call originates from the PSTN 15 (in this example a multimedia call), an initial SETUP message is sent which includes the called line identification (CLI) – in this case for a data call. [Step 1]. As mentioned above, the HLR contains a database entry corresponding to this CLI indicating the call type as data. The MSC 10 asks the HLR 12 for this call type (bearer capability) corresponding to the CLI, and sends a setup message to the MS 18 to inform it of the incoming call and of a default call type (e.g. a default data type) [Step 2]. The MS 18 responds by sending a CALL-CONF message after having checked the compatibility with the requested bearer capability [Step 3]. This message is forwarded to the PSTN as a CALL-PROC message by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and the default connection is made [Step 9].

Next, the MSC endeavours to determine the actual data type. In this example, upon connection, the V.8 / V.8bis signalling detector 41 of the MSC 10 interprets the PSTN originated V.8 / V.8bis signalling [Step 10]. The signalling related to the telecommunication services is mapped into corresponding GSM / UMTS signalling by the MSC 10 and, in this embodiment, the MSC instigates modification of the bearer using the GSM layer 3 call control protocol (GSM 04.08 para 9.3.13). In other words, in this case the detector 41 identifies the telecommunication service as a multimedia call (H.324) and the bearer service as a 28.8kbps transparent bearer service category. If necessary, connections within the MSC (including activation of modems) are rearranged for example as in the GSM Phase 1 proposed "alternate speech

and data" service. The GSM / UMTS speech bearer output to the mobile station speech channel is preferably blocked to prevent loudspeaker activation in the MS until the call type has been determined. However connection between the terminals is maintained.

Next, modem handshaking takes place [Step 11]. The, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth, and the MS 18 is informed of the requested call type [Step 12]. The MS returns a message to the MSC to complete the GSM / UMTS bearer modification process [Step 13]. The connection is now complete for multimedia communication between the PSTN terminal and MS 18 [Step 14]. Communication takes place via the MSC modem pool using the optimised radio bearer.

Mapping

Typical mapping operations performed by the MSC will now be described, firstly from V.8 to GSM and then optional mapping for V.8bis. As will be appreciated, this mapping is only exemplary and similar mapping could take place for future networks such as UMTS. GSM signalling is generally derived from ISDN, i.e. it is based on ITU-T Q.931 recommendation. So too are 3G telecommunication systems such as UMTS, hence, their particular compatibility with such mapping methods.

In this embodiment, information relating to the telecommunications service is mapped into the HLC (high level capability) information element in GSM (based on Q.931). Similarly, information relating to the bearer service is mapped into the BC (bearer capability) information element in GSM. Further details of the HLC, BC and also the LLC (low level capability element) are also provided in the following description of the mapping.

The V.8, V.8bis and GSM signalling information, which is relevant to the determination of telecommunication service types, is outlined below. The references refer to the following documents, the contents of which are incorporated herein by reference:

- [1] ITU-T Recommendation F.721 (08/92) - Videotelephony teleservice for ISDN
- [2] ITU-T Recommendation F.700 (07/96) - Framework Recommendation for audiovisual/multimedia services
- [3] ITU-T Recommendation V.8 (02/98) - Procedures for starting sessions of data transmission over the public switched telephone network
- [4] ITU-T Recommendation V.8bis (08/96) - Procedures for the identification and selection of common modes of operation between data circuit-terminating equipment (DCEs) and between data terminal equipment (DTEs) over the general switched telephone network and on leased point-to-point telephone-type circuits
- [5] ITU-T Recommendation H.324 (2/98) - Terminal for low bit rate multimedia communication
- [6] Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification, GSM 04.08 version 6.2.0 Release 1997
- [7] ITU-T Recommendation H.245 (2/98) - Control protocol for multimedia communication.

V.8 signalling to be mapped [3]

Table 2 in [3] lists the information categories that are available in V.8 signalling. As can be seen, the call-function octet has 3 option bits, and Table 3 in [3] illustrates how these option bits are used to identify particular call functions. As mentioned above, the information interpreted from the call function category can be mapped into the Q.931 HLC information element to provide the GSM network with information pertaining to the telecommunications service or call function and the bearer service.

Table 4 in [3] indicates the availability of PSTN V-Series modulation modes other than V.90. The availability is only shown if the modulation mode can be used with the indicated call function, and if it is desired to convey that capability to the remote DCE. For example, if an H.324 application is used, the use of a V.34 full duplex mode is mandatory, and the other options would not be indicated. The modulation mode information is only used between DCEs in order to find out the common modulation modes. After selection of a common modulation mode (e.g. V.34), the MSC/IWF determines the data rate from the modem (e.g. 28.8kbps) on the basis of how good the quality (BER) of the PSTN line is.

GSM (Q931-based) signalling onto which the above V8 signalling is mapped by the MSC

GSM specification 04-08 [6] defines the messages for circuit switched call control. In particular, section 9.3.23.1 in [6] defines the SETUP message content for mobile terminated call establishment. This message is sent over the network to the mobile station to initiate mobile terminated call establishment. The SETUP message contains relevant information elements for the BC (bearer capability), HLC (high level capability) and LLC (low level capability). As mentioned above, it is these information elements which the V.8 call function category information is mapped into.

BC

The purpose of the bearer capability information element is to describe the bearer service to be used in the connection. Figure 10.5.88 in [6] illustrates the BC element for GSM. This element contains 16 octets (8 bit units). Certain bits or coding points need to be stored in octets 3, 4, 6, 6a, 6c and 6d in order to support H.324, as outlined below.

Transfer mode (octet 3):

Bit

4

0 **circuit mode**

1 packet mode

- Circuit mode is selected

Duplex mode (octet 4)

Bit

4

0 half duplex

1 **full duplex**

- Full duplex is selected

Synchronous/asynchronous (octet 6)

Bit

1

0 **synchronous**

1 asynchronous

- Synchronous is selected

User rate (octet 6a)

Bits

4 3 2 1

0 0 0 1	0.3 kbit/s Recommendation X.1 and V.110
0 0 1 0	1.2 kbit/s Recommendation X.1 and V.110
0 0 1 1	2.4 kbit/s Recommendation X.1 and V.110
0 1 0 0	4.8 kbit/s Recommendation X.1 and V.110
0 1 0 1	9.6 kbit/s Recommendation X.1 and V.110
0 1 1 0	12.0 kbit/s transparent (non compliance with X.1 and V.110)
0 1 1 1	1.2 kbit/s/75 bit/s Recommendation V.23, (asymmetric) X.1, V.110.

The coding points shown above are used to indicate the user rate. At present there is no e.g. 28.8 kbps user rate available in GSM. However, Q.931 offers a wider set of user data rates that can be used when specifying the BC information element. (An outline of how the mapping might occur for the 28.8kbps and other unspecified data rates in GSM is outlined under the heading "Potential BC for other user rates").

Connection element (octet 6c)

Bit

7 6

0 0	transparent
0 1	non transparent (RLP)
1 0	both, transparent preferred
1 1	both, non transparent preferred

- Transparent is selected

Other modem type (octet 6d)

Bits

7 6

0 0 no other modem type specified in this field
 0 1 V.32bis
1 0 V.34

- V.34 is selected

Potential BC for other bit user rates.

Fixed network user rate (octet 6d)

Bit

5 4 3 2 1

0 0 0 0 0	Fixed network user rate not applicable/No meaning is associated with this value.
0 0 0 0 1	9.6 kbit/s Recommendation X.1 and V.110
0 0 0 1 0	14.4 kbit/s Recommendation X.1 and V.110
0 0 0 1 1	19.2 kbit/s Recommendation X.1 and V.110
0 0 1 0 0	28.8 kbit/s Recommendation X.1 and V.110
0 0 1 0 1	38.4 kbit/s Recommendation X.1 and V.110
0 0 1 1 0	48.0 kbit/s Recommendation X.1 and V.110(synch)
0 0 1 1 1	56.0 kbit/s Recommendation X.1 and V.110(synch) /bit transparent
0 1 0 0 0	64.0 kbit/s bit transparent

For an example data rate of 28.8 kbps, the element highlighted above might be used. So 28.8 is selected.

Acceptable channel codings (octet 6e), mobile station to network direction:

Bit

7

0 TCH/F14.4 not acceptable

1 TCH/F14.4 acceptable

If 14.4 is implemented then it can be selected.

Bit

6

0 Spare

Bit

5

0 TCH/F9.6 not acceptable

1 TCH/F9.6 acceptable

Normally, 9.6 is implemented as well

Bit

4

0 TCH/F4.8 not acceptable

1 TCH/F4.8 acceptable

4.8 exists even though not widely used

Acceptable channel codings (octet 6e), network to MS direction:

Bits 4 to 7 are spare and shall be set to "0".

This would mean that network cannot decide what kind of channel coding is used. This is required in the present case since networks initiate the call setup renegotiation. A change to current GSM implementation is needed to effect this.

Maximum number of traffic channels (octet 6e), MS to network direction:

Bits

3 2 1

0 0 0 1 TCH

0 0 1 2 TCH

0 1 0 3 TCH
 0 1 1 4 TCH
 1 0 0 5 TCH
 1 0 1 6 TCH
 1 1 0 7 TCH
 1 1 1 8 TCH

28.8kbps can be obtained by combining two 14.4 channels using HSCSD. This could also be done by combining three 9.6 channels.

Maximum number of traffic channels (octet 6e), network to MS direction:

Bits 1 to 3 are spare and shall be set to "0".

As above, this would mean that network is unable to decide what kind of channel coding is used, and would require a modification to GSM.

BC Information derived from Q931

BC information used in GSM in-band signalling is derived from Q.931 and modified for the purposes of GSM. The BC element discussed above is proposed to be used in UMTS in a frame of reference of this patent application.

In the Q.931 BC information element there exists one additional coding point which is needed and should be included in UMTS signalling. This coding point is User information layer 1 protocol (octet 5) and is described below:

User information layer 1 protocol (octet 5)

Bits

5 4 3 2 1

00001 CCITT standardised rate adaption V.110, I.460 and X.30. This implies the presence of octet 5a and optionally octets 5b, 5c and 5d as defined below.

00010	Recommendation G.711 μ -law
00011	Recommendation G.711 A-law
00100	Recommendation G.721 32 kbit/s ADPCM and Recommendation I.460.
00101	Recommendations H.221 and H.242
00110	Recommendations H.223 and H.245
00111	Non-ITU-T standardized rate adaption. This implies the presence of octet 5a and, optionally, octets 5b, 5c and 5d. The use of this code point indicates that the user rate specified in octet 5a is defined by the user. Additionally, octets 5b, 5c and 5d, if present, are defined consistent with the user specified rate adaption.
01000	ITU-T standardised rate adaption V.120. This implies the presence of octets 5a and 5b as defined below, and optionally octets 5c and 5d.
01001	CCITT standardised rate adaption X.31 HDLC flag stuffing. All other values are reserved.

- Recommendations H.223 and H.245 is selected

LLC

The low layer compatibility information element is illustrated in Figure 10.5.104 of [6]. The purpose of the low layer compatibility information element is to provide a means which should be used for compatibility checking by an addressed entity (e.g., a remote user or an interworking unit or a high layer function network node addressed by the calling user). The Low Layer Compatibility information element is transferred transparently by a PLMN between the call originating entity (e.g. the calling user) and the addressed entity.

Except for the information element identifier, the low layer compatibility information element is coded as in ETS 300 102-1.

This information element is not necessarily needed because the same coding can be conveyed in the BC.

HLC

The purpose of the high layer capability information element is to provide a means by which the remote user can check for compatibility.

The high layer compatibility information element is coded as shown in figure 10.5.102 and table 10.5.125 of [6].

The High Layer Compatibility information element is transported transparently by a PLMN between a call originating entity (e.g. a calling user) and the addressed entity (e.g. a remote user or a high layer function network node addressed by the call originating entity). However, if explicitly requested by the user (at subscription time), a network which provides some capabilities to realise teleservices may interpret this information to provide a particular service.

The following HLC code points can be found from the Q.931 recommendation:

High layer characteristics identification (octet 4)

Bits

7 6 5 4 3 2 1

0 0 0 0 0 0 1 Telephony

0 0 0 0 1 0 0 Facsimile Group 2/3 (Recommendation F.182 [68])

0 1 0 0 0 0 1 Facsimile Group 4 Class I (Recommendation F.184 [69])

- 0 1 0 0 1 0 0 Teletex service, basic and mixed mode of operation
(Recommendation F.230 [70]) and facsimile service Group 4,
Classes II and III (Recommendation F.184)
- 0 1 0 1 0 0 0 Teletex service, basic and processable mode of operation
(Recommendation F.220 [71])
- 0 1 1 0 0 0 1 Teletex service, basic mode of operation (Recommendation
F.200 [72])
- 0 1 1 0 0 1 0 Syntax based Videotex (Recommendations F.300 [73] and
T.102 [74])
- 0 1 1 0 0 1 1 International Videotex interworking via gateways or interworking
units (Recommendations F.300 and T.101 [75])
- 0 1 1 0 1 0 1 Telex service (Recommendation F.60 [76])
- 0 1 1 1 0 0 0 Message Handling Systems (MHS) (X.400 - Series
Recommendations [77])
- 1 0 0 0 0 0 1 OSI application (Note 2) (X.200 - Series Recommendations [78])
- 1 0 1 1 1 1 0 Reserved for maintenance (Note 4)
- 1 0 1 1 1 1 1 Reserved for management (Note 4)
- 1 1 0 0 0 0 0 Audio visual (Recommendation F.721 [79])
- 1 1 0 0 0 0 1 through 1 1 0 1 1 1 1 Reserved for audiovisual services [2]
- 1 1 1 1 1 1 1 Reserved

The F.700 Recommendation [2] provides a methodology for constructing multimedia services which is timely and responsive to the needs of both the End-User and Service Provider. This methodology links generic End-User application requirements with the established set of network independent building blocks or other communications capabilities being developed within ITU-T. The procedures described in this Recommendation are intended for use in developing a series of General Service Recommendations which combine the required communication tasks and media components into an architecture for generic services (e.g. for Multimedia Conferencing Service, Multimedia Distribution Service, etc.). Where applicable Recommendations are not yet available, this methodology can be used as the basis for a

structured dialogue between End-Users and Service Providers in arriving at a responsive service solution.

Bits 1100001 through 1101111, specified in F.700, could be used for e.g. H.324 code point or a totally new codepoint could be designed for UMTS use.

V.8bis signalling to be mapped [4]

Table 6-2 in [4] lists the standard information categories that are available in V.8bis signalling. It comprises categories such as data and H.324 multimedia terminal to readily cater for such future teleservices. The coding for these teleservices are illustrated in Tables 6-3 and 6-5 of [4]. One advantage of the V.8bis capability exchange is that, in most cases, it enables terminals to ascertain very quickly when operation in H.324 mode is desired. This is because V.8bis capabilities indicate only the most basic and commonly used modes. If an H.324 operation mode not signalled by V.8bis is desired, the terminal must complete call establishment and perform a H.245 [7] capabilities exchange to determine if the far-end terminal supports the desired mode.

Within the Rec. V.8bis Communications Capabilities (CC) field for H.324, the CC field is formatted into one or more sub-fields. Each sub-field ends with the octet in which bit [n] is set to 1. Following the first sub-field, the remaining sub-fields, if present, shall appear in the same order in which the bits indicating their presence are transmitted. The actual bit assignments can be seen from [4].

In the first sub-field the following bits are allocated:

Name	Meaning
Video	Shall be set only if bi-directional video is supported per Rec. H.324 (sec. 6.6).

Audio	Shall be set only if bi-directional audio is supported per Rec. H.324 (sec. 6.7).
Encryption	Shall be set only if encryption is supported per Rec. H.324 (sec. 9.2).
Data	Indicates that a data subfield is present. Shall be set only if one or more bits in the data subfield are set.

Possible future allocations include Profiles (new subfield).

In the Data subfield, the following bits are allocated:

Name Meaning

- T.120 Shall be set only if T.120 conferencing is supported per Rec. H.324 (sec. 6.8.2.1).
- T.84 Shall be set only if T.84 still image transfer is supported per Rec. H.324 (sec. 6.8.2.2).
- T.434 Shall be set only if T.434 file transfer is supported per Rec. H.324 (sec. 6.8.2.3).
- V.42 Shall be set only if V.42 user data is supported per Rec. H.324 (sec. 6.8.1.2/6.8.2.6).
- V.14 Shall be set only if V.14 user data is supported per Rec. H.324 (sec. 6.8.1.1/6.8.2.6).
- PPP Shall be set only if IETF Point-to-Point protocol is supported via the Network Layer Protocol Identifier (NLPID) per Rec. H.324 (sec. 6.8.2.5).
- T.140 Shall be set only if T.140 Text Conversation Protocol for Multimedia Application is supported per Rec H.324 (sec 6.8.2.8).

Other modes beside those indicated in V.8bis, such as unidirectional modes, may be supported by terminals as signalled via H.245 capabilities exchange.

With V.8bis signalling can also be used when the call is first started in speech mode and after that it is switched to e.g. H.324 mode. For this reason, the MSC/IFW must all the time be able to listen the possible inband signalling coming from PSTN modem. The switch of service then initiates the bearer renegotiation in UMTS side where the "old" bearer is accomplished according to QoS parameters needed to H.324 call.

Mapping between UMTS and PSTN/ISDN

In this section different information elements and their codings are described. These codings must be mapped in the interface of either PSTN / UMTS or ISDN / UMTS.

Necessary PSTN codings in the frame of reference of the patent application:

V.8

	<i>Call function category (Octet – "callf0")</i>
100	PSTN Multimedia Terminal (Bits 567)
	<i>Modulation modes category (Octet – "modn0")</i>
1	V.34 duplex availability (Bit 6)

V.25ter

	<i>Modulation control commands</i>
	Modulation reporting control (+MR)
+MCR: V34	+MCR: <carrier>
+MRR: 28800	+MRR: <rate>

V.8bis

Standard information field - {SPar(1)} coding

Standard information field – Data {NPar(2)} coding (Octet 2)

1 Rec. V.34 duplex mode (Bit 5)

Standard information field - {SPar(1)} coding

Standard information field – H.324 multimedia terminal {NPar(2)} coding

1 Video (Bit 1)

Standard information field - {SPar(1)} coding

Standard information field – H.324 multimedia terminal {NPar(2)} coding

1 Audio (Bit 2)

Necessary ISDN codings (in a case V.140 signalling is needed) in the frame of reference of the patent application:

V.140 inband signals consist of HDLC-framed PDUs defined using ASN.1 syntax according to Recommendation X.680 and coded according to the packed encoding rules of Recommendation X.691.

The purpose why V.140 signalling is used is that there exist networks that fail to send out band signalling messages end to end. V.140 signalling used in ISDN does more or less the same thing as V.8/V.8bis signalling in PSTN.

The capabilitySet field of the roleAndCapability PDU contains a sequence of one or more Capability structures, each expressing the terminal's ability to work in a particular multimedia or other communication protocol. The transmitter shall include the complete list of modes in which it is currently able to operate. The list of possible modes is defined in Annex A of V.140, and

may be extended in the future. Capabilities shall be listed in order of preference, from most-preferred to least-preferred. In our case the h324AnnexD should be the first (or only one) of the listed capabilities in capabilitySet field.

The receiving terminal can answer the transmitting terminal of the selected mode by using modeSelect PDU.

In the following the syntax of PDUs using ASN.1 notation is described [V.140 Annex A]. The "code point" of our choice is presented with bigger font.

```
HDISPATCH DEFINITIONS AUTOMATIC TAGS ::=
BEGIN
```

```
-- Export all symbols
```

Abstract

1. The first part of the document is a list of 10 items, each consisting of a number followed by a name. The names are: 1. John Doe, 2. Jane Smith, 3. Bob Johnson, 4. Alice Brown, 5. Charlie White, 6. David Green, 7. Emily Black, 8. Frank Grey, 9. Grace Pink, 10. Henry Blue.

- Top level PDUs

1. The first part of the document is a list of 10 items, each consisting of a number followed by a name. The names are: 1. John Doe, 2. Jane Smith, 3. Bob Johnson, 4. Alice Brown, 5. Charlie White, 6. David Green, 7. Emily Black, 8. Frank Grey, 9. Grace Blue, 10. Henry Red.

HDispatchPDU	::=CHOICE
{	
nonStandard	NonStandardMessage,
roleAndCapability	RoleAndCapabilityMessage,
modeSelect	Mode,
youChoose	NULL,
modeSelectAcknowledge	NULL,
terminate	TerminateMessage,
...	
}	
RoleAndCapabilityMessage	::=SEQUENCE
{	
role	CHOICE
{	
originate	NULL,
unknown	NULL,
answer	NULL,
...	
},	

```

    arbitrationField      INTEGER (0..4294967295), -- 32 bit
                           random #
    capabilitySet          SEQUENCE SIZE (1..65535) OF
                           Capability,
    ...
}

Capability                ::= CHOICE
{
    nonStandard            NonStandardParameter,
    isdn                   CHOICE
    {
        isdnCapability     IsdnCapability,
        multilinkAdditionalConnection NULL, -- Express this cap alone to
                                                force association of this
                                                channel with
                                                --an existing call
                                                --"BONDING" protocol
    },
    is13871                SEQUENCE
    {
        withIsdnCapability IsdnCapability,
        ...
    },
    h244                   SEQUENCE -- channel
    {
        aggregation protocol
        {
            withIsdnCapability IsdnCapability,
            ...
        },
        ...
    },
    ...
}

IsdnCapability            ::= CHOICE
{
    g711aLaw               SEQUENCE {...},
    g711uLaw               SEQUENCE {...},
    h320                   SEQUENCE {...},
    h324AnnexD             SEQUENCE {...},
    h324Multilink          SEQUENCE {...},
    group4Fax              SEQUENCE {...},
    t120                   SEQUENCE {...},
    t140                   SEQUENCE {...},
    v110                   SEQUENCE {...},
    v120                   SEQUENCE {...},
    rfc1661                SEQUENCE {...},
    {
        withH323           BOOLEAN,
        ...
    }
}

```

-- text chatting protocol


```

    ...
    },
    ...
}

{
    nonStandard                NonStandardParameter,
    plainIsdnMode              IsdnMode,
    h244                       IsdnMode,
    is13871                    IsdnMode,        --    BONDING
protocol
    multilinkAdditionalConnection SEQUENCE
    {
        callAssociationNumber    INTEGER (0..4294967295),
        ...
    },
    ...
}

```

```

IsdnMode ::= CHOICE
{
    nonStandard                NonStandardParameter,
    g711aLaw                  SEQUENCE {...},
    g711uLaw                  SEQUENCE {...},
    h320                      SEQUENCE {...},
    h324AnnexD                SEQUENCE {...},
    h324Multilink             SEQUENCE {...},
    group4Fax                  SEQUENCE {...},
    t120                      SEQUENCE {...},
    rfc1661                   SEQUENCE {...},
    ...
}

```

```

TerminateMessage ::= SEQUENCE
{
    cause                     CHOICE
    {
        nonStandard                NonStandardParameter,
        timerExpiration             NULL,
        roleCollision               NULL,
        noSuitableModes             NULL,
        invalidModeSelected         NULL,
        protocolViolation           NULL,
        modeNotAvailable            NULL,
        ...
    },

```

```

    ...
}

--
=====
-- Non standard Message definitions
--
=====

NonStandardMessage          ::=SEQUENCE
{
    nonStandardData          NonStandardParameter,
    ...
}

NonStandardParameter        ::=SEQUENCE
{
    nonStandardIdentifier    NonStandardIdentifier,
    data                     OCTET STRING
}

NonStandardIdentifier       ::=CHOICE
{
    object                   OBJECT IDENTIFIER,
    h221NonStandard         SEQUENCE
    {
        t35CountryCode      INTEGER (0..255),-- country, per T.35
        t35Extension        INTEGER (0..255),-- assigned ationally
        manufacturerCode    INTEGER (0..65535)-- assigned
nationally
    }
}

```

Necessary UMTS (GSM) codings in the frame of reference of the patent application:

Bearer Capability

0 *Bearer Capability Information Element*
 Transfer mode (octet 3)
 Circuit mode (Bit 4)

1 *Bearer Capability Information Element*
 Duplex mode (octet 4)
 Full duplex (Bit 4)

Bearer Capability Information Element

0	Synchronous/Asynchronous (octet 6) Synchronous (Bit 1)
00100	<i>Bearer Capability Information Element</i> Fixed network user rate (octet 6d) 28.8 kbps (Bits 54321)
1	<i>Bearer Capability Information Element</i> Acceptable channel codings (octet 6e) TCH/F14.4 acceptable (Bit 7)
1	<i>Bearer Capability Information Element</i> Acceptable channel codings (octet 6e) TCH/F9.6 acceptable (Bit 5)
1	<i>Bearer Capability Information Element</i> Acceptable channel codings (octet 6e) TCH/F4.8 acceptable (Bit 4)
001	<i>Bearer Capability Information Element</i> Maximum number of traffic channels (octet 6e) 2 TCH (Bits 321)
00	<i>Bearer Capability Information Element</i> Connection element (octet 6c) Transparent (Bits 76)
10	<i>Bearer Capability Information Element</i> Other modem type (octet 6d) V.34 (Bits 76)
00110	<i>Bearer Capability Information Element</i> User information layer 1 protocol (octet 5) Recommendations H.223 and H.245 (Bits 54321)

The latest information coding point is not present in current GSM BC information element. It is taken from Q.931 and should be added to future UMTS BC information element.

High Layer Compatibility

1100001	<i>High Layer Compatibility Information Element</i> High layer characteristics identification (octet 4) PSTN Multimedia Terminal (Bits 7654321)
---------	---

The present invention includes any novel feature or combination of features disclosed herein either explicitly or any generalisation thereof irrespective of whether or not it relates to the claimed invention or mitigates any or all of the problems addressed.

In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. For example, the reduced numbering scheme is not restricted to only one or two numbers for call type differentiation. It will be appreciated that the reference to H.324 throughout this text is purely exemplary and that the invention is also applicable to other data types.

Claims

1. A switch for establishing a call between a terminal of an originating network and a terminal of a terminating network, the switch comprising:
 - an input for receiving call identification information in a first format from the originating network;
 - reformatting means for reformatting received call identification information into a second format;
 - an output means for outputting the call identification information in the second format over the terminating network; and
 - connection means for completing a connection, suitable for the identified call, between the terminals.
2. A switch as claimed in claim 1, wherein the call identification information comprises call type information.
3. A switch as claimed in claim 2, wherein the call type information comprises telecommunications service information.
4. A switch as claimed in any preceding claim, wherein the call identification information comprises bearer service information.
5. A switch as claimed in claim 4, wherein the reformatting means for reformatting the received bearer service information is arranged to negotiate the bearer of the terminating network to match that of the originating network.
6. A switch as claimed in any preceding claim, wherein the first format is an in band format.
7. A switch as claimed in any preceding claim, wherein the second format is an out band format.

8. A switch as claimed in any preceding claim, wherein the terminating network is digital.
9. A switch as claimed in any preceding claim, wherein the originating network is analogue.
10. A switch as claimed in any preceding claim, wherein one of the networks is a wireless communications network.
11. A switch as claimed in claim 10, wherein the wireless communication network is a universal mobile telecommunications system (UMTS) network.
12. A switch as claimed in claim 10, wherein the wireless communication network is a GSM network.
13. A switch as claimed in claim 11 or 12, wherein the switch is a mobile switching centre.
14. A switch as claimed in any of claims 10 to 13, comprising a transcoder.
15. A switch as claimed in any of claims 10 to 14 wherein the wireless communications network is the terminating network.
16. A switch as claimed in any of claims 1 to 7, wherein one of the networks is a fixed line network.
17. A switch as claimed in claim 16, wherein the fixed line network is a PSTN network.
18. A switch as claimed in claim 16, wherein the fixed line network is an ISDN network.

19. A switch as claimed in any of claims 16 to 18, wherein the fixed line network is the originating network.
20. A switch as claimed in any preceding claim, further comprising:
means, coupled to the input, for determining primary call type information on the basis of a subscriber number, for forwarding first primary call identification information to the output, and for forwarding further primary call identification information to the reformatting means.
21. A method for establishing a call between a terminal of an originating network and a terminal of a terminating network, the method comprising:
receiving call identification information in a first format from the originating network;
reformatting received call identification information into a second format;
outputting the call identification information in the second format over the terminating network; and
completing a connection, suitable for the identified call, between the terminals.
22. A method as claimed in claim 21, wherein the call identification information comprises call type information.
23. A method as claimed in claim 22, wherein the call type information comprises telecommunications service information.
24. A method as claimed in any of claims 21 to 23, wherein the call identification information comprises bearer service information.
25. A method as claimed in claim 24, wherein reformatting received call identification information comprises negotiating the bearer of the terminating network to match that of the originating network.

26. A method as claimed in any preceding claim, wherein the first format is an in band format.
27. A method as claimed in any preceding claim, wherein the second format is an out band format.
28. A method as claimed in any preceding claim, wherein the terminating network is digital.
29. A method as claimed in any preceding claim, wherein the originating network is analogue.
30. A method as claimed in any of claims 21 to 29, wherein one of the networks is a wireless communications network.
31. A method as claimed in claim 30, wherein the wireless communication network is a universal mobile telecommunications system (UMTS) network.
32. A method as claimed in claim 30, wherein the wireless communication network is a GSM network.
33. A method as claimed in any of claims 21 to 27, wherein one of the networks is a fixed line network.
34. A method as claimed in claim 33, wherein the fixed line network is a PSTN network.
35. A method as claimed in claim 33, wherein the fixed line network is an ISDN network.

36. A method as claimed in any of claims 33 to 35, wherein the fixed line network is the originating network.
37. A method for establishing a call between a terminal of an originating network and a terminal of a terminating network, the method comprising:
- establishing a call of a predetermined type;
 - transmitting call identification information in a first format from the originating terminal to the terminating network;
 - reformatting received call identification information into a second format;
 - transmitting the call identification information in the second format to the terminating terminal; and
 - establishing a connection, suitable for the identified call, between the terminals.
38. A method as claimed in any of claims 21 to 37, further comprising:
- determining primary call identification information on the basis of a subscriber number;
 - providing a predetermined connection if the primary call identification corresponds to the call identification of the predetermined connection; and
 - performing the reformatting, transmitting and establishing steps if the primary call information is different.
39. A switching system for establishing a call between a terminal of an originating network and a terminal of a terminating network, the switching system comprising:
- means for receiving call identification information in a first format from the originating network;
 - means for reformatting received call identification information into a second format;
 - means for transmitting the call identification information in the second format over the terminating network; and

connection means for completing a connection, suitable for the identified call, between the terminals.

40. A switch for establishing a call between a terminal of an originating network and a terminal of a terminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 23 of the accompanying drawings.

41. A system for establishing a call between a terminal of an originating network and a terminal of a terminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 23 of the accompanying drawings.

42. A method for establishing a call between a terminal of an originating network and a terminal of a terminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 23 of the accompanying drawings.

1 / 24




FIG. 1




FIGURE 2

3/24





FIGURE 3



When V.8 CF code
0x21 is received from
PSTN, MSC sure that
originating end supports
H.324 application

FIGURE 4

5 / 24




FIG. 5




FIGURE 6

PSTN-MS direct call involvement, single-numbering Scheme





FIGURE 7

PSTN-MS direct call, single-numbering Scheme



When V.8 CF code
0x21 is received from
PSTN, MSC sure that
originating end supports
H.324 application

FIGURE 8

9/24

MS-PSTN Speech First, with Changeover Using V.8bis




FIGURE 9

MS - PSTN direct call without V.8bis involvement




FIGURE 10

MS - PSTN direct call without V.8bis involvement




FIGURE 11

ISDN - UMTS




FIGURE 12

ISDN - UMTS without end-to-end HLC




FIGURE 13

UMTS - ISDN




FIGURE 14

UMTS - ISDN without end-to-end HLC




FIGURE 15

ISDN - UMTS without end-to-end LLC




FIGURE 17

18/24

UMTS - ISDN




FIGURE 18

UMTS - ISDN without end-to-end LLC




FIGURE 19

UMTS - UMTS




FIGURE 20

UMTS - 2G

WO 00/51387

PCT/IB00/00229

21/24




FIGURE 21




FIGURE 22

23/24




FIGURE 23

24/24

V.8		UMTS	
100	Call function category (Octet – "callf0") PSTN Multimedia Terminal (Bits 567)	Bearer Capability Bearer Capability Information Element Transfer mode (octet 3) Circuit mode (Bit 4)	0
1	Modulation modes category (Octet – "modn0") V.34 duplex availability (Bit 6)	Bearer Capability Information Element Duplex mode (octet 4) Full duplex (Bit 4)	1
V.25ter		Bearer Capability Information Element Synchronous/Asynchronous (octet 6) Synchronous (Bit 1)	0
	Modulation control commands Modulation reporting control (+MR)	Bearer Capability Information Element Fixed network user rate (octet 6d) 28.8 kbps (Bits 54321)	00100
+MCR: V34 +MCR: <carrier> +MRR: 28800 +MRR: <rate>			
V.8bis		Bearer Capability Information Element Acceptable channel codings (octet 6e) TCH/F14.4 acceptable (Bit 7)	1
1	Standard information field - {SPar(1)} coding Standard information field – Data {NPar(2)} coding (Octet 2) Rec. V.34 duplex mode (Bit 5)	Bearer Capability Information Element Acceptable channel codings (octet 6e) TCH/F9.6 acceptable (Bit 5)	1
1	Standard information field - {SPar(1)} coding Standard information field – H.324 multimedia terminal {NPar(2)} coding Video (Bit 1)	Bearer Capability Information Element Acceptable channel codings (octet 6e) TCH/F4.8 acceptable (Bit 4)	1
1	Standard information field - {SPar(1)} coding Standard information field – H.324 multimedia terminal {NPar(2)} coding Audio (Bit 2)	Bearer Capability Information Element Maximum number of traffic channels (octet 6e) 2 TCH (Bits 321)	001
		Bearer Capability Information Element Connection element (octet 6c) Transparent (Bits 76)	00
		Bearer Capability Information Element Other modem type (octet 6d) V.34 (Bits 76)	10
		High Layer Compatibility	
		High Layer Compatibility Information Element High layer characteristics identification (octet 4)	
		PSTN Multimedia Terminal (Bits 7654321)	1100001

Figure 24

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/38 H04Q11/04 H04Q3/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 34437 A (TELEFONAKTIEBOLAGET L M ERICSSON) 18 September 1997 (1997-09-18)	1,6-10, 12-21, 26-30, 32-42
Y	abstract	
A	page 7, line 4 -page 8, line 11 claim 1; figure 1	2-4, 22-24 5,11,25, 31
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 July 2000

Date of mailing of the international search report

25/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gijssels, W

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/00229

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>EP 0 843 454 A (LUCENT TECHNOLOGIES INC) 20 May 1998 (1998-05-20)</p> <p>abstract column 4, line 39 -column 5, line 14 claims 1,2; figure 1 ---</p>	<p>1,6,9, 16-21, 26,29, 33-42</p>
Y	<p>WO 98 58475 A (TOSHIBA K K) 23 December 1998 (1998-12-23)</p> <p>abstract & EP 0 921 659 A (TOSHIBA K K) 9 June 1999 (1999-06-09) column 12, line 8 -column 13, line 10 claims 28,31,34; figures 1-7 ---</p>	<p>2-4, 22-24</p>
A	<p>EP 0 771 095 A (AT & T CORP) 2 May 1997 (1997-05-02)</p> <p>abstract claims 1-3; figures 1,2 ---</p>	<p>1-42</p>
A	<p>LINDBERGH D: "THE H.324 MULTIMEDIA COMMUNICATION STANDARD" IEEE COMMUNICATIONS MAGAZINE, vol. 34, no. 12, 1 December 1996 (1996-12-01), pages 46-51, XP000636453 PISCATAWAY, NJ, US ISSN: 0163-6804 ---</p>	
P,X	<p>DE 198 15 430 A (DEUTSCHE TELEKOM MOBILNET GMBH) 14 October 1999 (1999-10-14)</p> <p>abstract column 3, line 16-41 claim 1; figures 1A,1B ---</p>	<p>1,6-10, 12-21, 26-30, 32-42</p>
E	<p>US 6 073 018 A (SALLBERG K) 6 June 2000 (2000-06-06)</p> <p>abstract column 7, line 8 -column 8, line 38 tables 2,3A,3B claims 1,6,9; figure 1 -----</p>	<p>1-4, 6-10, 12-24, 26-30, 32-42</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. ational Application No

PCT/IB 00/00229

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9734437 A	18-09-1997	US 5890064 A	30-03-1999
		AU 711632 B	21-10-1999
		AU 2049097 A	01-10-1997
		CA 2247979 A	18-09-1997
		CN 1217861 A	26-05-1999
		EP 0886984 A	30-12-1998
EP 0843454 A	20-05-1998	JP 10190743 A	21-07-1998
WO 9858475 A	23-12-1998	CN 1234933 T	10-11-1999
		EP 0921659 A	09-06-1999
EP 0771095 A	02-05-1997	US 5724355 A	03-03-1998
		CA 2184209 A	25-04-1997
		JP 9214564 A	15-08-1997
DE 19815430 A	14-10-1999	AU 4132499 A	25-10-1999
		WO 9952255 A	14-10-1999
US 6073018 A	06-06-2000	AU 1722199 A	28-06-1999
		WO 9930518 A	17-06-1999